

## CERTIFICATE OF PRODUCT CONFORMITY

*Dubai Central Laboratory Department (DCLD) of Dubai Municipality,*

*hereby attests that the product(s)*

**IN-SITU FORMED SPRAYED APPLIED POLYURETHANE (PUR) FOAM**

*(Details as per the attached Scope of Certification)*

*manufactured by:*


**AL SAAD INSULATION MATERIALS.**

**NBAD Bldg. Fujairah, U.A.E.**

*have been assessed in accordance with DCLD Document Ref. No. RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:*

**BS EN 14315-1: 2013**

*Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark to the above-mentioned product(s).*



for / **ENGR. AMIN AHMED AMIN**

**Director, Dubai Central Laboratory Department**

**Dubai Municipality**

Verify:



**Certificate No: CL16020363**

**Valid Until: 07 May 2019**



**Current Issue Date: 08 May 2018**

**Original Issue Date: 08 May 2016**

F-IC-2031 REV 12

*The attached Scope of Certification bearing the same Certificate No. forms an integral part of this Certificate.*

*This Certificate is an electronic document, subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.*



## DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL16020363

<b>Certificate Issued To:</b>	<b>AL SAAD INSULATION MATERIALS</b> NBAD Building, Dibba, Fujairah, UAE
<b>Applicable Standard Specification:</b>	BS EN 14315-1:2013 – Thermal Insulating Product for Buildings In-situ Formed Sprayed Rigid Polyurethane (PUR) and PIR Foam Products
<b>Applicable Specific Rules:</b>	RD-DP21-2187 (IC) “Specific Rules for Certification of In-Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per EN14315-1:2013) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1	In-Situ Formed Sprayed Polyurethane (PUR) Foam Products “CFC Free” **	AL SAAD	In-Situ Formed Sprayed Polyurethane (PUR) Foam Core Density 35-40 Kg/m <sup>3</sup> Min. Thickness = 45 mm k-value: 0.027 W/(K•m)* With a minimum Compressive Strength of 250 kPa Product Code: PU EN14315-1-DS(TH)3-CS(10/Y)250-MU(25)

NOTE 1: \* Maximum k-value measured at 35°C temperature and 60% relative humidity condition

NOTE 2: This document forms part of the Certificate of Product Conformity bearing the same Certificate Number.

NOTE 3: \*\* CFC Free as per declaration from the company, in accordance with the Dubai Green Building Regulations and Specifications

NOTE 4: Applicable only to In Situ Formed Sprayed PUR Insulation Foam used as part of combo-roofing system where in the insulation material layer is fully covered by concrete layer. Accordingly there is no requirement for testing the fire safety requirements as per clause [6.3.8] of the UAE Fire and Life Safety Code of Practice 2016.

Original Issue Date : 08 May 2016  
Current Issue Date : 08 May 2018  
Valid Until : 07 May 2019

ARIF HUSAIN AL MARZOOQI  
Head of Products Conformity Assessment Section  
Dubai Central Laboratory Department