

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

TECHNICAL METALIC PROFILE FACTORY L.L.C

P. O. BOX: 6559, AJMAN INDUSTRIAL AREA 1, AJMAN, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13165: 2012

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL16020404
Valid Until: 14/11/2019



Current Issue Date: 15/11/2018
Original Issue Date: 15/11/2016

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION Rev 01
FOR CERTIFICATE NO. CL16020404**

Certificate Issued To : **TECHNICAL METALLIC PROFILE FACTORY LLC**
P. O. BOX: 6559, AJMAN INDUSTRIAL AREA 1, AJMAN, UAE

Applicable Standard Specification: BS EN 13165:2012 –Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products - Specification

Applicable Specific Rules : RD-DP21-2124 (IC) “Specific Rules for Certification of Factory Made Rigid Polyurethane BS EN 13165: 2012) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1	Factory made rigid polyurethane (PUR) foam for Thermal Insulation CFC Free <i>(See Note 4)</i>	TMPF	PUR Thermal Insulation Foam Minimum Thickness: 20 mm; Nominal Length: 3000 mm (min); Nominal Width: 1200 mm (min); Apparent Density 35 Kg/m ³ (min); Thermal Conductivity (max) – Initial Value: 0.025 W/(m*K); Age Value: 0.023 W/(m*K) @35 °C & 60% RH PUR - EN13165 – T2 – DS(70,90)1 – CS (10/Y) 100 – MU150 Manufactured with aluminum foil facing and flat or corrugated aluminum metal sheet on both or either sides

NOTE 1: The above products shall bear the DCL Conformity Mark applied on each individual product.



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION Rev 01
FOR CERTIFICATE NO. CL16020404**

NOTE 2: This certification covers only the PUR foam within the panel

NOTE 3: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 4: In compliance with 2017 Al Sa'fat Green Building Evaluation System

NOTE 5: The revision was made due to the separation of Fire Safety requirements from Al Sa'fat Certification requirements

NOTE 6: This supersedes the scope of certification issued on 15 November 2018

Original Issue Date : 15 November 2016

Current Issue Date : 24 March 2019

Valid Until : 14 November 2019

ARIF HUSAIN AL MARZOOQI
Products Conformity Assessment Section Manager
Dubai Central Laboratory Department