

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

GULF PAINTS & ADHESIVES FACTORY

Sanaiya Industrial Area, Al Ain, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).

for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL16020408
Valid Until: 11/12/2019



Current Issue Date: 12/12/2018
Original Issue Date: 12/12/2016

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL16020408

Certificate Issued To:

GULF PAINTS & ADHESIVES FACTORY

Sanaiya Industrial Area, Al Ain, UAE

Applicable Standard Specification:

2017 Al Sa'fat - Dubai Green Building Evaluation System

Applicable Specific Rules:

RD-DP21-2180-(IC) Specific Rules for Certification of Low Emitting Materials (Paints, Coatings, Adhesives, Sealants) As per the 2017 Al Sa'fat Dubai Green Building Evaluation System.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Interior matt walls and ceiling paint (Gloss <25@60°C)	Falco Silk	<p>Water Base Paint for Interior Application VOC (AL SA'FAT-DGBES limit is Max. 30 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury & Lead (AL SA'FAT-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg</p>
		Falco Silk Emulsion	
		Falco Latex Matt	
		Falco Wall Plaster	
		Falco Stucco Putty H.Q.	
		Falco Stucco Putty	
		Falco Texo Plaster	
		Falco Spray Plaster	
		Falco Bitumen Emulsion	
		Falco GPI Acrylic Texture	
		Falco GPI Acrylic Putty	
		Falco GPI Acrylic Spray Compound	
		Falco latex Antiseptic*	
		Falco Emulux*	
Falco Emulux Antiseptic*			
Falco latex Anti fungus*			
2	Interior glossy walls and ceiling paint (Gloss >25@60°C)	Falco Climate Tough	<p>Water Base Paint for Interior Application VOC (AL SA'FAT-DGBES limit is Max. 100 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury & Lead (AL SA'FAT-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg</p>
		Falco Silk Hygiene	
		Falco Silk Diamond	
		Falco Emulsion	
		Falco Silk Matt	



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL16020408

3	Primers	Falco Sealer Primer	Water Base Paint for Interior & Exterior Application VOC (AL SA'FAT-DGBES limit is Max. 30 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
		Falco Tex Primer	
		Gulf Shield Primer	
		Gulf Shield Tex Primer	
		Gulf Shield Penetrating Primer W.B.	
		Falco Acrylic Primer	
		Falco White Primer	
		Falco GP Acrylic Primer	Solvent Base Paint for Interior & Exterior Application VOC (AL SA'FAT-DGBES limit is Max. 350 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg)
		Falco Penetrating Primer	
		Falco Penetrating Primer SB	
		Falco Red Oxide Primer	
		Falco Epoxy Sealer	
		Falco Epoxy Sealer "Solvent Free"	
		Falco GPHB Primer	
Gulf Silane Siloxane	Solvent Base Paint for Interior & Exterior (intermediate) Application VOC (AL SA'FAT-DGBES limit is Max. 500 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg)		
Gulf Guard ZPHB Primer			
Gulf Guard Zinc Chromate Primer			
Falco General Epoxy Primer			
4	One Pack Performance Coating	Falco Road Marking	Solvent Base Paint for Interior & Exterior (intermediate) Application VOC (AL SA'FAT-DGBES limit is Max. 500 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg)
		Falco Thermo Plastic Acrylic Floor Paint	
5	Two Pack Reactive Performance Coating for Specific End Use such as Floors	Falco Guard Concrete Floor Coating	Solvent Base Paint for Interior Application VOC (AL SA'FAT-DGBES limit is max.500 g/l) Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg),
		Falco Epoxy Floor Paint "Solvent Free"	
		Falco Polyurethane Floor Coating	
		Falco General Purpose Epoxy	
		Gulf Guard Epoxy –Water Tank	
		Falco Super Thane	
Falco PU Membrane			



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME
SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL16020408

		Falco GPI Epoxy Spray Texture	<p align="center">Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg</p>
		Falco GPI Epoxy Putty	
6	Exterior Walls for Mineral Substrate	Gulf Shield Silk Gloss	<p align="center">Water Base Paint for Exterior Application</p> <p align="center">VOC (AL SA'FAT-DGBES limit is max. 40 g/l)</p> <p>Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg)</p> <p align="center">Formaldehyde ≤ 10 mg/kg <u>Color: White</u></p> <p>LRV Class 1 (= > 45) - can be used in 75-100% surfaced to be coated/painted</p> <p align="center">(See Note 3 & 4)</p>
		Gulf Shield Medium Tex	
		Gulf Shield Fine Tex	
		Falco Tex III	
		Falco Mezario Tex	
		Gulf Shield Superior	
		Gulf Shield Silk	
		Gulf Shield Elastomeric Silk	
		Gulf Shield Silk Hard Top	
		Falco Silicon Emulsion	
		Falco Tex II	
		Falco Light Tex	
		Falco Non Cracking Tex	
		Falco Roma Tex H.Q.	
		Gulf Shield Heritage Traditional Tex	
		Gulf Shield Ultra Tex	
		Falco Roof Coating	
		Falco Roc	
		Gulf Shield Thermo*	
		Gulf Shield Silk Matt *	
		Falco Acryl	<p align="center">Solvent Base Paint for Exterior (intermediate) Application</p> <p align="center">VOC (AL SA'FAT-DGBES limit is Max. 430 g/l)</p> <p>Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg)</p>
		Falco Thane	
		Falco Lac Enamel	
		Falcon I	



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME
SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL16020408

7	Decorative Effect Coating	Falco Glamorous	Water Base Paint for Exterior (intermediate) Application VOC (AL SA'FAT-DGBES limit is Max. 200 g/l)
		Falco Heritage Putty	Heavy metals: Cadmium and Chromium (AL SA'FAT-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (AL SA'FAT-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
--Nothing Follows--			

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE2: The above product shall bear the DCL Conformity Mark.

NOTE 3: SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-AL SA'FAT.

NOTE 4: For colors/Types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-AL SA'FAT.

SRI Class 1 (> 78) – “Can be Used in 75 - 100% of surface to be coated – Sloped or Flat Roof”

SRI Class 2 (29<78) - “Can be Used in 75 - 100% of surface to be coated – Sloped Roof”

SRI Class 3 (< 29 or untested) – “Can be Used in 0 – 25% of surface to be coated – Sloped or Flat Roof provided the remaining area is Class 1 or 2”

LRV Class 1 (=>45) – “Can be used in 75-100% of surface to be /painted/coated”

LRV Class 2 (<45 or untested) – “Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1”.

NOTE 5: *- Newly added products.

Original Issue Date : 12 December 2016

Current Issue Date : 12 December 2018

Valid Until : 11 December 2019

ARIF HUSAIN AL MARZOOQI
Products Conformity Assessment Section Manager.
Dubai Central Laboratory Department