

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

LOOTAH METAL SECTION PROFILE LLC

New Industrial Area, Ajman, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13165: 2012

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL17020472
Valid Until: 02/07/2019



Current Issue Date: 03/07/2018
Original Issue Date: 03/07/2017

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION Rev 01
FOR CERTIFICATE NO. CL17020472**

Certificate Issued To: LOOTAH METAL SECTION PROFILE LLC
New Industrial Area, Ajman, UAE

Applicable Standard Specification: BS EN 13165:2012 –Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products - Specification

Applicable Specific Rules: RD-DP21-2124 (IC) Specific Rules For Certification of Factory Made Polyurethane Rigid Foam Thermal Insulation as per (BS EN 13165:2012) Through Factory Assessment

S/N	Product Description	Brand Name	Product Details
1	Factory made polyurethane (PUR) rigid foam for Thermal Insulation CFC Free (See Note 4)	LOOTAH METALS SECTION PROFILE (SANDWICH PANELS)	Polyurethane (PUR) Thermal Insulation Foam Nominal Thickness – 30 to 200 mm; Length (max) – 12000 mm; Width (max) – 1200 mm; Apparent Density - 40 kg/m ³ (min); Thermal conductivity@ 35°C (max): Initial Value - 0.026 & Aged Value - 0.028 W/(m*K) Code: PUR - EN13165 – T1 – DS(70,90)1 – CS(10/Y)100 – μ60 to 80 Manufactured with aluminum foil facing and flat or corrugated aluminum metal sheet on both or either sides

NOTE 1: The above products shall bear the DCL Conformity Mark (applied on each product or on the packaging).



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION Rev 01
FOR CERTIFICATE NO. CL17020472**

NOTE 2: This certification covers only the PUR foam within the panel

NOTE 3: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 4: In compliance with 2017 Al Sa'fat Green Building Evaluation System

NOTE 5: The revision was made due to the separation of Fire Safety requirements from Al Sa'fat Certification requirements

NOTE 6: This supersedes the scope of certification issued on 03 July 2018

Original Issue Date : 03 July 2017

Current Issue Date : 24 March 2019

Valid Until : 02 July 2019

ARIF HUSAIN AL MARZOOQI
Products Conformity Assessment Section Manager
Dubai Central Laboratory Department