

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality,

hereby attests that the product(s)

LOW EMITTING MATERIALS (COATINGS, SEALANTS & ADHESIVES)

(Details as per the attached Scope of Certification)

manufactured by:


DUBAI ADHESIVE MATERIAL FACTORY LLC

Industrial Area No. 17, Sharjah, U.A.E.

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark to the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN

Director, Dubai Central Laboratory Department

Dubai Municipality

Verify:



Certificate No: CL17020474

Valid Until: 09 July 2019



Current Issue Date: 10 July 2018

Original Issue Date: 10 July 2017

DM-DCLD-F-IC-2031 REV 13

The attached Scope of Certification bearing the same Certificate No. forms an integral part of this Certificate.

This Certificate is an electronic document, subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

SCOPE OF CERTIFICATION – REVISION 01

FOR CERTIFICATE NO. CL17020474

Certificate Issued To **DUBAI ADHESIVE MATERIAL FACTORY LLC.**
Industrial Area No. 17, Sharjah, UAE

Applicable Standard Specification: 2017 Al Sa'fat Dubai Green Building Evaluation System
Applicable Specific Rules: RD-DP21-2180-(IC) Specific Rules for Certification of Low Emitting Materials (Paints, Coatings, Adhesives, Sealants) As per the 2017 Al Sa'fat Dubai Green Building Evaluation System.

S/N	Product Description	Brand Name	Product Details
1	One-pack performance coatings (Sub-category 9)	DEUTHANE TOP COAT – GRAY DEUTHANE PU TOP COAT*	Water Base Coatings for Exterior Application (Topcoat for Combo Roof System) VOC (GBRS limit is max.140 g/l) SRI Class 2 (29<78) - "Can be Used in 75 - 100% of surface to be coated – Sloped Roof" LRV =45% (min) <u>*SRI and LRV (See Note 3)</u>
		DEUTHANE TOP COAT – WHITE DEUTHANE PU TOP COAT*	Water Base Coatings for Exterior Application (Topcoat for Combo Roof System) VOC (GBRS limit is max.140 g/l) SRI =78 (min) {SRI Class 1 as per Annex B of RD-DP21-2180(IC)} LRV =45% (min) <u>*SRI and LRV (See Note 3)</u>
		RICHPROOF 5000 AWAZEL ACRYLIC COAT* DEUPROOF – SP* DEUPROOF 5000*	Water Base Coatings for Exterior Application (Acrylic Coating for Waterproofing) VOC (GBRS limit is max.140 g/l)
		DEUTHANE BLK-PU DEUTHANE PU 500* DEUTHANE PU 250*	Water Base Coatings for Exterior Application (Waterproofing for Wet Areas) VOC (GBRS limit is max.140 g/l)
2	One-pack performance coatings (Sub-category 9) Coating (other types)	DEUBIT PROOF 300** DEUBITPROOF SBS 989**	Water Base Coatings for Interior Application VOC (GBRS limit is max.140 g/l)

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION – REVISION 01
FOR CERTIFICATE NO. CL17020474

S/N	Product Description	Brand Name	Product Details
3	Two Pack Reactive Performance Coating for Specific End Use such as Floors (Sub-category 10)	DEUCRETE CWP AWAZEL CEMENT ACRYLIC COAT* RICHFLEX*	Water Base Coatings for Exterior Application (WATERPROOFING FOR WET AREAS) VOC (GBRS limit is max.140 g/l)
4	Two Pack Reactive Performance Coating for Specific End Use such as Floors (Sub-category 10) Paint (Interior/Not Exposed)	DEUPOXY TOP COAT** DEUPOXY 700**	Water Base Coatings for Interior Application VOC (GBRS limit is max. 140 g/l) Heavy metals: Cadmium and Chromium VI (GBRS limit < 500 mg/Kg), Arsenic, Mercury and Lead (GBRS limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
5	ADHESIVES - Fiberglass	DEUCOAT 30-36	Water Base Adhesives for Specific Application (HVAC LAGGING ADHESIVES) VOC (GBRS limit is max. 80 g/l)
		CRAYCOAT 30-36 WESTRON 30-36* CARE COAT 30 36*	Water Base Adhesives for Specific Application (HVAC LAGGING ADHESIVES) VOC (GBRS limit is max. 80 g/l)
		DEUCOAT 30-36 AF DEUCOAT 30-40*	Water Base Adhesives for Specific Application (HVAC ANTIFUNGAL LAGGING ADHESIVES) VOC (GBRS limit is max. 80 g/l)
		CRAYCOAT 30-36 AF CARE COAT 30-36 AF*	Water Base Adhesives for Specific Application (HVAC ANTIFUNGAL LAGGING ADHESIVES) VOC (GBRS limit is max. 80 g/l)
		DEUCOAT 60-95 DEUCOAT 60-96*	Water Base Adhesives for Specific Application (VAPOR BARRIER CANVAS COATING) VOC (GBRS limit is max. 80 g/l)
		DEUCOAT 85-70	Water Base Adhesives for Specific Application (WEATHERPROOF HVAC COATING) VOC (GBRS limit is max. 80 g/l)

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION – REVISION 01
FOR CERTIFICATE NO. CL17020474

S/N	Product Description	Brand Name	Product Details
5	ADHESIVES - Fiberglass	DEUCOAT 30-80	Water Base Adhesives for Specific Application (WATERPROOF HVAC COATING ADHESIVE) VOC (GBRS limit is max. 80 g/l)
		DEUCOAT DUCT GLUE 81-10**	Water Base Adhesives for Specific Application VOC (GBRS limit is max. 80 g/l)
		DEUFIX E12 ** DEUFIX E 11** DEUCOAT DUCT GLUE 1080**	Water Base Adhesives for Specific Application VOC (GBRS limit is max. 80 g/l)
6	SEALANT - Architectural	DEUSEAL 32-17 (GRAY) DEUSEAL 32-17(WHITE)* DEUPHIDE*	Water Base Sealant for Specific Application (ACRYLIC DUCT SEALANT) VOC (GBRS limit is max.250 g/l)

*-newly added brandname

** - newly added products

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark.

NOTE 3: For colors/Types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-GBRS.*

SRI Class 1 (> 78) – “Can be Used in 75 - 100% of surface to be coated – Sloped or Flat Roof”

SRI Class 2 (29<78) - “Can be Used in 75 - 100% of surface to be coated – Sloped Roof”

SRI Class 3 (< 29 or untested) – “Can be Used in 0 – 25% of surface to be coated – Sloped or Flat Roof provided the remaining area is Class 1 or 2”

LRV Class 1 (=>45) – “Can be used in 75-100% of surface to be /painted/coated”

LRV Class 2 (<45 or untested) – “Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1”.

NOTE 4: This supersedes the scope of certification issued on 10 July 2018.

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION – REVISION 01
FOR CERTIFICATE NO. CL17020474**

Original Issue Date : 10 July 2017
Current Issue Date : 12 November 2018
Valid Until : 09 July 2019



ARIF HUSAIN AL MARZOOQI
Products Conformity Assessment Section Manager
Dubai Central Laboratory Department