

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Mineral Wool Insulation

(Details as per the attached Scope of Certification)

manufactured by:

SAUDI INTERNATIONAL INSULATION MANUFACTURING COMPANY (SIIMCO)

Yanbu Industrial City 11574

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13162: 2012

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).

for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL17020484
Valid Until: 23/07/2019



Current Issue Date: 24/07/2018
Original Issue Date: 24/07/2017

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME
SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020484 Rev 01

Certificate Issued To

SAUDI INTERNATIONAL INSULATION MANUFACTURING COMPANY (SIIMCO)

P.O. Box 57774 Yanbu Industrial City 11574 , KSA

Applicable Standard Specification:

BS EN 13162:2012 – Thermal Insulation Products for Buildings – Factory Made Mineral Wool (MW) Products - Specification

Applicable Specific Rules:

RD-DP21-2130 (IC) “Specific Rules for Certification of Factory Made Mineral Wool Thermal Insulation Products (as per BS EN 13162:2012) Through Factory Assessment”.

| S/N | Product Description | Product Brand | Product Details |
|-----|--|-------------------|---|
| 1 | Mineral wool (rock wool) Slab/Board (CFC Free)* | KIMMCO ISOVER* | <p>Stone mineral wool COMFORT slab/board without facing for all applications.</p> <p>Nominal Thickness: (30 - 220) mm</p> <p>Reaction to Fire Classification: Class A (ASTM E84) and Class A1 (BSEN13501-1)</p> <ol style="list-style-type: none"> Nominal Density, (30 – 59) kg/m³, k-value: 0.040 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(0.5) – MU1 Nominal Density, (60 – 69) kg/m³, k-value: 0.039 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – MU1 Nominal Density, (70 – 79) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – MU1 Nominal Density, (80 – 89) kg/m³, k-value: 0.037 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – MU1 Nominal Density, (90 – 99) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – MU1 Nominal Density, (100 – 200) kg/m³, k-value: 0.039 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(15) – MU1 |
| | | KIMMCO ISOVER* | <p>Stone mineral wool COMFORT slab/board with Aluminum Foil Scrim facing for all applications.</p> <p>Nominal Thickness: (30 - 220) mm</p> <p>Reaction to Fire Classification: Class A (ASTM E84) and Class A1 (BSEN13501-1)</p> <ol style="list-style-type: none"> Nominal Density, (30 – 59) kg/m³, k-value: 0.040 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(0.5) – Z3 Nominal Density, (60 – 69) kg/m³, k-value: 0.039 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – Z3 Nominal Density, (70 – 79) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – Z3 Nominal Density, (80 – 89) kg/m³, k-value: 0.037 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – Z3 Nominal Density, (90 – 99) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – Z3 Nominal Density, (100 – 200) kg/m³, k-value: 0.039 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(15) – Z3 |



DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020484 Rev 01

| | | | |
|---|---|-------------------|--|
| 2 | Mineral wool (rock wool) Roll/Blanket | KIMMCO ISOVER* | <p>Stone mineral wool COMFORT Roll/blanket with Aluminum Foil Scrim facing for all applications.</p> <p>Nominal Thickness: (30 - 100) mm</p> <p>Reaction to Fire Classification: Class A (ASTM E84) and Class A1 (BSEN13501-1)</p> <ol style="list-style-type: none"> Nominal Density, (30 – 59) kg/m³, k-value: 0.040 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(0.5) – Z1 Nominal Density, (60 – 69) kg/m³, k-value: 0.039 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – Z1 Nominal Density, (70 – 79) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(5) – Z1 Nominal Density, (80 – 89) kg/m³, k-value: 0.037 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – Z1 Nominal Density, (90 – 100) kg/m³, k-value: 0.038 W/(m.K) MW – EN 13162 – T4 – DS(70,90) – CS(10) – Z1 |
|---|---|-------------------|--|

Note 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

Note 2: The above products shall bear the DCL Conformity Mark (applied on each product or on the packaging).

Note 3: Maximum k-value measured at 35°C temperature and 60% relative humidity condition

Note 4: *newly added products to scope of certification and this scope replace the scope issued on 24 July 2018

Note 5: *This product is complying with "UAE Fire and Life Safety Code of Practice 2018 edition "*

Original Issue Date: 24 July 2017

Current Issue Date: 13 Jan 2019

Valid Until : 23 July 2019

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department