

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality,

hereby attests that the product(s)

IN-SITU FORMED SPRAYED POLYURETHANE (PUR) FOAM PRODUCTS

(Details as per the attached Scope of Certification)

Manufactured by:


Noor Al Khaldiah Tech. Cont L.L.C

P.O.Box 68650 – Dubai Branch

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) “General Rules for DM third party product certification system through factory assessment” and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 14315-1: 2013

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark to the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN

Director, Dubai Central Laboratory Department

Dubai Municipality

Verify:



Certificate No: CL18020605

Valid Until: 02 July 2019



Current Issue Date: 03 July 2018

Original Issue Date: 03 July 2018

DM-DCLD-F-IC-2031 REV 13

The attached Scope of Certification bearing the same Certificate No. forms an integral part of this Certificate.

This Certificate is an electronic document, subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL18020605**

Certificate Issued To: Noor Al Khaldiah Tech. Cont L.L.C
P.O.Box 68650 – Dubai Branch

Applicable Standard Specification: EN 14315-1:2013 – Thermal Insulating Product for Buildings In-situ Formed Sprayed Rigid Polyurethane (PUR) and PIR Foam Products

Applicable Specific Rules: RD-DP21-2187 (IC) “Specific Rules for Certification of In-Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per EN14315-1:2013) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1	Spray-Applied Rigid Polyurethane (PUR) Foam Products “CFC Free” *	ROOFING SYSTEM	In Situ Formed Sprayed PUR Insulation Foam Core Density = 40kg/m ³ ; Min thickness 35 mm Thermal conductivity (max) value - 0.0241 W/(m*K) @ 35C; with Minimum Compressive strength of 150 Kpa Code : PU-EN 14315 -1-DS(TH)2 -CS(10/Y)150-μ85

NOTE1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE2: The above product shall bear the DCL Conformity Mark.


NOTE 3: *CFC Free as per declaration from the company, in accordance with the Dubai Green Building Regulations and Specification.

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL18020605**

NOTE 4: *Applicable only to In Situ Formed Sprayed PUR Insulation Foam used as part of Combo-roofing system where in the insulation material layer is fully covered by Concrete layer. Accordingly there is no requirement for testing the fire safety Requirements as per clause [6.3.8] of the UAE Fire and Life Safety Code of Practice 2017.*

Original Issue Date : 03 July 2018
Current Issue Date : 03 July 2018
Valid Until : 02 July 2019



ARIF HUSAIN AL MARZOOQI
Head of Products Conformity Assessment Section
Dubai Central Laboratory Department