

 GOVERNMENT OF DUBAI	Organization Unit	Public Health & Safety Department	الوحدة التنظيمية:	 بلدية دبي DUBAI MUNICIPALITY
	Form sheet title:	Guidelines for Approval of Swimming Pool Plans	اسم النموذج :	
	Doc Ref.	DM-PH&SD-P7-TG02	رقم النموذج :	

Side handrails extending above and returning to the horizontal surface of the pool deck shall be provided at each side of each ladder or recessed steps.

- Pools with steps may only be permitted in shallow pools not exceeding 1m.

2. *Showers and Foot Baths*

Showers and foot baths should be provided at 25 m intervals around the perimeter of the pool. Signs must be posted asking bathiers to shower before using the pool.

3. *Toilets and Changing Room Facilities*

All swimming pool shall be provided with toilet and changing room facilities.

4. *Diving Towers, Platforms and Boards*

1. At least 5 m of unobstructed headroom above the diving boards or towers shall be provided.
2. Diving boards or platforms shall be entirely covered with non slip materials.
- 3.. The minimum depth of water for any diving board placed 1m or less above the water shall be 2.5. m. The diving depth for boards above 1 m. shall be increased 0.3 for each meter or fraction thereof above 1 m.

Horizontal separation of 3 m shall be provided between adjacent diving boards and between any diving board and the side wall.

5. *Lighting*

Pools, designed for use at night shall be illuminated either by underwater or overhead lighting or both to ensure that all areas of the bottom of the pool as well as the entire volume of the pool are well illuminated without creating any reflections, glares, burns, electrical shock or mechanical injury to both the swimmers and life guards.

Electrical circuits shall have earth leakage circuit breaker and be shown in the drawing.

6. *Depth Marking*

Depth of water shall be plainly marked on the edge of the deck or pool wall at maximum points, at points of break in slope.

