



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

In-situ Formed Sprayed PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

AL ITQAN COATING & INSULATION MATERIALS CO. LLC PO Box 48198, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 14315-1: 2013

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**

ADCIAC 001-CB-PRD

CL17020430 Certificate No: Valid Until: 25/02/2021



Current Issue Date: 26/02/2020 Original Issue Date: 26/02/2017



DM-DCLD-F-IC-2031 Rev 17

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020430

Certificate Issued To: AL ITQAN COATING & INSULATION MATERIALS CO. LLC

P. O. Box 48198, Dubai, UAE

Applicable Standard Specification: BS EN 14315-1:2013 – Thermal Insulating Product for

Buildings In-situ Formed Sprayed Rigid Polyurethane PUR and

PIR Foam Products

Applicable Specific Rules: DM-DCLD-RD-DP21-2187 (IC) "Specific Rules for Certification

of In-Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per EN14315-1:2013) Through Factory

Assessment".

S/N	Product Description	Brand Name	Product Details
			Min. Density : 40 kg/m³
1	Spray-Applied	SAFE ROOFING	Thickness: 30 mm (min)
	Rigid	SYSTEM	k-value: 0.026 W/(K•m)* (max) @ 35°C & 60% RH
	Polyurethane		With a minimum Compressive Strength of 100 kPa
	(PUR) Foam		·
	Products		Dimensional Stability (DS(TH)2
	"CFC Free" *		Short term water absorption by partial immersion: 0.05 kg/m2 (max)
			Product Code:
			PU EN14315-1-DS(TH)2-CS(10/Y)100-MU(30)

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same Certificate Number.

NOTE 2: * Maximum k-value measured at 35°C temperature and 60% relative humidity Condition.

NOTE 3: ** CFC Free as per declaration from the company, in compliance with Clause 701.01 (1) of the 2017

Al Sa'fat Dubai Green Building Evaluation System.





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020430

Original Issue Date : 26 February 2017

Current Issue Date : 26 February 2020

Valid Until : 25 February 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department