

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

In-situ Formed Sprayed PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)


manufactured by:

GREEN SEAL INSULATION LLC
P.O. BOX 236438, DUBAI, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 14315-1: 2013

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL17020431
Valid Until: 22/02/2022



Current Issue Date: 23/02/2021
Original Issue Date: 23/02/2017



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020431

Certificate Issued To:	GREEN SEAL INSULATION LLC P.O. Box 236438, Dubai, UAE.
Applicable Standard Specification:	BS EN 14315 - 1: 2013 – Thermal insulating products for buildings – In situ formed sprayed polyurethane (PUR) and Polyisocyanurate (PIR) foam products
Applicable Specific Rules:	DM-DLCD-RD-DP21-2187 (IC) “Specific Rules for Certification of In Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per BS EN14315-1:2013) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1.	In-Situ Formed Sprayed Polyurethane (PUR) Foam Products CFC Free **	GREEN SEAL	In Situ Formed Sprayed Polyurethane (PUR) Foam Core Density = 35 Kg/m ³ (min) Minimum Thickness = 35 mm Thermal Conductivity value: 0.025 W/(K-m)* With a minimum Compressive Strength of 100 kPa Product Code: PU EN14315-1-DS(TH)2- CS (10/Y) 100-MU25

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020431

NOTE 1: *This document forms part of the Certificate of Product Conformity bearing the same Certificate Number.*

NOTE 2: ** Maximum k-value measured at 35°C temperature and 60% relative humidity Condition.*

NOTE 3: *** CFC Free as per declaration from the company, in compliance with Clause 701.01 (1) of the 2017 Al Sa'fat Dubai Green Building Evaluation System.*

Original Issue Date: 23 February 2017

Current Issue Date: 23 February 2021

Valid Until: 22 February 2022

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager
Dubai Central Laboratory Department