

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

In-situ Formed Sprayed PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

DOLPHIN WATER PROOFING & INSULATION LLC

P.O. Box: 430208, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 14315-1: 2013

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



001-CB-PRD

Certificate No: CL17020468
Valid Until: 13/06/2021



Current Issue Date: 14/06/2020
Original Issue Date: 14/06/2017



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020468

Certificate Issued To: DOLPHIN WATER PROOFING & INSULATION LLC
P.O. Box: 430208, Dubai, UAE

Applicable Standard Specification: BS EN 14315-1:2013 – Thermal Insulating Product for Buildings
In-situ Formed Sprayed Rigid Polyurethane (PUR) and PIR Foam Products

Applicable Specific Rules: DM-DCLD-RD-DP21-2187 (IC) “Specific Rules for Certification of In-Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per EN14315-1:2013) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1	Spray-Applied Rigid Polyurethane (PUR) Foam Products “CFC Free” *	SAFE ROOFING SYSTEM	Min. Density : 40 kg/m ³ , Thickness: 45-150mm k-value: 0.025 W/(K·m)* (max) @ 35°C & 60% RH With a min. Compressive. Strength of 100 kPa Dimensional Stability (DS(TH)2 Short term water absorption by partial immersion: 0.1 kg/m ² (max) Product Code: PU EN14315-1-DS(TH)2-CS(10/Y)100-MU(25)

NOTE1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE3: *CFC Free as per declaration from the company, in compliance with 2017 Al Sa’fat – Dubai Green Building Evaluation System.

Original Issue Date : 14 June 2017

Current Issue Date : 14 June 2020

Valid Until : 13 June 2021



ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager
Dubai Central Laboratory Department