



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

FALCON CHEMICALS LLC AL HATTA HIBAB ROAD, JABEL ALI INDUSTRIAL AREA NO: 3, DUBAI, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: Valid Until:

CL18020593 28/05/2022



Current Issue Date: 29/05/2021 Original Issue Date: 29/05/2018



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.





DM-DCLD-F-IC-2031 Rev 18







DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020593

Certificate Issued To: FALCON CHEMICALS LLC

Al Hatta Hibab Road, Jabel Ali Industrial Area No. 3, Dubai, UAE

Applicable Standard Specification: 2017 Al Sa'fat – Dubai Green Building Evaluation System.

Applicable Specific Rules: DM-DCLD-RD-DP21-2180-(IC) Specific Rules for FA Certification of

Low Emitting Materials as per Al Sa'fat - Dubai Green Building

Evaluation System.

Evaluation System.				
s/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS	
	Primers (Category 7)	LAVADEC FR	Water based Primer for Interior/Exterior Applications: VOC (Al Sa'fat DGBES limit is max.30 g/l)	
1		LAVATEX 100	Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg	
		LAVASOL	Solvent based Primer for Interior/Exterior Applications: VOC (Al Sa'fat DGBES limit is max.350 g/l) Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead Al Sa'fat DGBES limit < 100 mg/Kg)	
	One -pack Performance Coatings (Category 9)	LAVACOOL ECOTHANE COLORTOP	Water Base Coating for Interior/Exterior Applications: VOC (Al Sa'fat DGBES limit is max 140 g/l)	
		LAVASHIELD GP	LRV Class: Class 2	
		LAVASHIELD SUPER	SRI Class: Class 2 White Color - See Note #3	
2		LAVATHANE	White Color - See Note #3	
		LAVAFLEX 1K	Water Base Coating for Interior/Exterior Applications	
		LAVADEC 600 FRC	VOC (Al Sa'fat DGBES limit is max 140 g/l) LRV Class: Class 1 – White Color SRI Class: Class 1 – White Color White Color - See Note #3	





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020593

		LAVATEX R- 10	
		FLEXKOTE	Water Base Coating for Interior Applications:
		LAVATEX 2000	VOC (Al Sa'fat DGBES limit is max 140 g/l)
		LAVATEX RBE	
		ECOPOXY 310	Solvent Base Coating for Interior Application:
		ECOPOXY 410	VOC (Al Sa'fat DGBES limit is max 500 g/l)
3	Two -pack Reactive	LAVAFLEX 2K	Water Base Coating for Interior / Exterior Application: VOC (Al Sa'fat DGBES limit is max 140 g/l)
	Performance		LRV Class: Class 1 – White Color
	Coatings for		SRI Class: Class 1 – White Color
	specific end such		White Color - See Note #3
	as floor (Category 10)		Solvent Base Coating for Interior / Exterior Application:
		ECOPOXY 610	VOC (Al Sa'fat DGBES limit is max 500 g/l)
			LRV Class: Class 1 – White Color
			See Note #3
4	CERAMIC TILE -	ULTRATILE UTA	Ceramic Tile Adhesive - VOC
		ULTRATILE PD	(Al Sa'fat DGBES limit is max 65 g/l)
		ULTRATILE ST	
5	MULTI PURPOSE -	MARBLEX	Multi-Purpose construction Adhesive - VOC (Al Sa'fat DGBES limit is max 70 g/l)
		ULTRABOND F 440	
	CONST. ADTIESTVE	ULTRABOND HD	(Al Sa lat DODES lillit is lilax 10 g/l)
	ARCHITECTURAL	ULTRAGROUT	Architectural Non Porous Sealants - VOC
			Alcintectural Non Porous Sediants - VOC
6	NON POROUS	ULTRAGROUT	(A) Solfat DGDES limit in many 250 m/l)
6	NON POROUS SEALANTS	ULTRAGROUT	(Al Sa'fat DGBES limit is max 250 g/l)
		ULTRAGROUT BONDEX FRP	(Al Sa'fat DGBES limit is max 250 g/l) DRY WALL & PANEL ADHESIVES – VOC
7	SEALANTS		
	SEALANTS DRY WALL &	BONDEX FRP	DRY WALL & PANEL ADHESIVES – VOC





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020593

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark.

NOTE 3: For colors/types not covered by the Scope, SRI/LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the 2017 Al Sa'fat –Dubai Green Building Evaluation System.

- o SRI Class 1 (≥ 78) "Can be Used in 75 100% of surface to be coated Sloped or Flat Roof"
- o SRI Class 2 (29<78) "Can be Used in 75 100% of surface to be coated Sloped Roof"
- SRI Class 3 (< 29 or untested) –"Can be Used in 0–25% of surface to be coated Sloped or Flat Roof"
- LRV Class 1 (≥45) "Can be used in 75-100% of surface to be /painted/coated"
- LRV Class 2 (<45) "Can be used in 0-25% of surface to be painted/coated"

Original Issue Date: 29 May 2018

Current Issue Date: 29 May 2021

Valid Until: 28 May 2022

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department