

Organization/Unit: بدبي المركزي (الدرة مختبر دبي المركزي (Dubai Central Laboratory Department (Dubai Central Laboratory Department (Specific Rules For Certification of Rendering and Plastering Mortar (as per BS EN 998-1:2016) Through Factory Assessment (Doc Ref. DM-DCLD-RD-DP21-2193 (IC)



	Doc Ret.	رقم الوثيقة : DM-DCLD-RD-DP21-2193 (IC)	
Issue Date	Rev. No.	Summary Of Amendments	
16/08/2015	0	First draft for comments	
05/06/2016	0	Second draft for comments	
27/08/2016	1	Issue for use	
10/01/2018	2	Reflect technical committee comments for reaction to Fire and durability tests	
		requirements.	
29/08/2018	3	Correction in Clause 6 Fee Schedule	
24/03/2019	4	Updated as per new DM logo	
25/03/2020	5	New amendment as per BS EN998-1:2016 standard, changing font type and some	
		editorial changes	
04/08/2020	6	Add the options for initial audit by the approved CAB and remotely by PCAS. Adding	
		definition for authorized auditor. Update for the new numbering system and followed	
		terminologies. Add provision for accepting valid test reports	

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 1 of 9



1. GENERAL

1.1 INTRODUCTION

- 1.1.1 This document prescribes the specific rules for the implementation of the DM Third Party Product Certification

 Scheme through factory assessment as applied to the specific product(s) identified herein, taking into consideration the applicable normative references and standard specifications.
- 1.1.2 The applicant shall comply with these specific rules, and to those already mentioned in the "General Rule for DM Third Party Product Certification System Scheme Through Factory Assessment" DM-DCLD-RD-DP21-2001 (IC).
- 1.2 SCOPE
- 1.2.1 This specific rule specifies requirements for certifying the technical properties of rendering and plastering mortar, including in factory made rendering/plastering mortar based on inorganic binders for external (rendering) and internal (plastering) use on walls, ceilings, columns and partitions.
- 1.2.2 It does not cover mortars where calcium sulphate binder is the principle active binding agent.
- 1.2.3 Special fire resistant- and acoustical mortars, mortars for structural repair and surface treatments of building elements such as materials for smoothing or trueing, paints, coatings, thin-layer organic renders/plasters and prefabricated units (e.g. plaster boards) are not dealt with in this European Standard.
- 1.3 PRODUCT IDENTIFICATION AND APPLICABLE STANDARD/NORMATIVE REFERENCE

1.3.1 Product Name: Rendering and plastering mortar

1.3.2 Applicable standard/Normative reference: BS EN 998-1:2016

Specification for mortar for masonry Rendering and

plastering mortar.

1.3.3 Additional references:

ISO 9001- Quality Management System – Requirements
ISO 19011-Guidelines for Auditing Management Systems

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 2 of 9



1.4 DEFINITION OF TERMS

The definitions given in BS EN 998-1:2016, DM-DCLD-RD-DP21-2001 (IC) and in addition, the following shall apply:

- 1.4.1 Independent Testing Laboratory Dubai Central Laboratory Department or any testing laboratory recognized by the DCLD-PCAS.
- 1.4.2 Independent Test test performed or conducted by the recognized Independent Testing Laboratory
- 1.4.3 Standard Specification BS EN 998-1:2016 Specification for mortar for masonry (Rendering and plastering mortar)
- 1.4.4 Product Quality Assurance Plan a document being agreed upon both by the Client and DCLD-PCAS, being used to ensure continuous compliance of the certified product.
- 1.4.5 QMS Quality Management System aligned with the requirements of ISO 9001 Standard.
- 1.4.6 Client Manufacturer of Rendering and Plastering Mortar
- 1.4.7 DM Certification Body: Dubai Central Laboratory Department-Products Conformity Assessment Section (DCLD-PCAS)
- 1.4.8 Authorized auditor: is any approved auditor by DCLD-PCAS either internal within DCLD or external (Approved CAB's auditor or approved auditor based on a signed contract)

2. REQUIREMENTS FOR CERTIFICATION

- 2.1 APPLICATION
- 2.1.1 The client shall apply to DCLD-PCAS for the Certification and authorization to use the DCL Conformity Mark.
- 2.1.2 Application forms shall be submitted to DCLD-PCAS together with the following documents
 - a. Industrial Trade License
 - b. Complete product description and specifications
 - c. Brief Description of Manufacturing Process
 - d. Copy of the Quality Manual (if available) (Controlled Copy)

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 3 of 9

~ 2 8 × ~ ~	Organization/Unit:	إدارة مختبر دبي المركزي Dubai Central Laboratory Department	الوحدة التنظيمية:	
GOVERNMENT OF DUBAI	Document Title:	Specific Rules For Certification of Rendering and Plastering Mortar (as per BS EN 998-1:2016) Through Factory Assessment	عنوان الوثيقة:	بلدية دبي
	Doc Ref.	DM-DCLD-RD-DP21-2193 (IC)	رقم الوثيقة:	

- e. Vicinity Map and Factory Layout
- f. Valid Certification to ISO 9001 (If available)
- g. List of personnel and their designation

Total number of effective personnel involved in manufacture of the product (technical, managerial and support personnel).

- i. List of available testing equipment and tests conducted internally
- j. Others
- 2.1.3 Separate application shall be submitted for each product type or group of products that refers to a different specific rules

2.2 FACTORY OPERATION

2.2.1 Quality Management System

The client shall have a Quality Management System that is aligned to the requirements of ISO 9001 standard.

NOTE: Having a certificate of ISO 9001 is not a mandatory requirement; however the structure of the manufacturer's QMS shall be in line with its requirements.

2.2.2 Laboratory

The client shall have a quality assurance laboratory to carry out factory production control testing to ensure that product complies with the requirements of the standard specification. The laboratory can be part of the factory facilities, or, can be through a documented agreement with an accredited laboratory. The following are the minimum tests to be carried out to check product compliance with the requirements of standard specification.

- a. Dry bulk density
- b. Compressive strength
- c. Adhesion
- d. Adhesion after weathering cycles
- e. Capillary water absorption (for mortar used externally)
- f. Water penetration after capillary water absorption
- g. Water permeability on relevant substrates after weathering cycles (after 48 h)
- h. Water vapor permeability coefficient μ for mortars intended to be used in external elements
- i. Thermal Conductivity (for mortars intended to be used in elements subject to thermal requirements)
- j. Reaction to fire (if applicable and according to clause 5.2.2 of BS EN 998-1:2016 standard)
- k. Durability (If applicable)

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 4 of 9



2.3 INITIAL FACTORY AUDIT

Initial factory audit will be carried out by duly authorized auditor(s) which will cover auditing of the quality

management system to verify its compliance with the requirements of ISO 9001, in addition to verify the implementation of DCLD-PCAS certification's requirements. Where possible; the audit can be carried out remotely as per (DM-DCLD-RD-DP21-2098 (IC) Guidelines for Remote Audit) or as per the related approved guidelines which are followed by the approved outsourced CAB.

NOTE: An independent certification to ISO 9001 issued by a QMS certification body recognized by DCLD-PCAS may be considered as having satisfied this requirement; however, DCLD-PCAS reserves the right to carry out verification audit to confirm that the factory is in compliance with the QMS requirements, in addition to the requirements of DCLD certification schemes and rules.

2.3.2 Factory audit shall be conducted by designated audit team in accordance with ISO 19011 – Guidelines for Auditing Management Systems.

2.4 PRODUCT EVALUATION

- 2.4.1 Sampling
- 2.4.1.1 Sampling for initial testing shall be shall be taken randomly by the authorized auditor from the products to be certified (sizes and quantity to be determined) either from production lines or the factory warehouse, in accordance with the requirements of BS EN998-1.
- 2.4.1.2 Three sets of sample per product per type shall be subjected to testing; the first set, where possible, will be tested in the plant witnessed by a duly authorized auditor, the second set will be sent to DCLD-PCAS approved Independent Testing Laboratory. The third set will be kept by the manufacturer as reference for future use.
- 2.4.1.3 Sample(s) for independent test shall be packed/sealed and signed in the presence of the authorized auditor and shall be submitted to DCLD-PCAS approved lab.

2.4.2 Product Evaluation and testing

Referring to Table 2 of the Standard Specifications (EN 998-1: 2016) and the Type classification of product to be certified, all applicable tests shall be carried out as per test methods mentioned below:

2.4.2.1 Dry bulk density as per EN 1015-10

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 5 of 9



Organization/Unit:	إدارة مختبر دبي المركزي Dubai Central Laboratory Department	الوحدة التنظيمية:	
Document Title:	Specific Rules For Certification of Rendering and Plastering Mortar (as per BS EN 998-1:2016) Through Factory Assessment	عنوان الوثيقة:	بلدية دبي
Doc Ref.	DM-DCLD-RD-DP21-2193 (IC)	رقم الوثيقة:	



2.4.2.2	compressive strength as per EN 1015-11
2.4.2.3	adhesion as per BSEN 1015-12
2.4.2.4	Adhesion after weathering cycles as per EN 1015-21
2.4.2.5	Capillary water Absorption (for mortars intended to be used in external elements)) as per BS EN1015-18
2.4.2.6	water penetration after capillary water absorption test (in mm) as per BS EN1015-18
2.4.2.7	Water permeability on relevant substrates after weathering cycles (ml/cm2 after 48 h) as per BS EN 1015-21.
2.4.2.8	water vapour permeability coefficient μ (for mortars intended to be used in external elements) as per EN1015-19 ^{ab} .
2.4.2.9	Thermal conductivity mean $\lambda 10$,dry,mat -values (W/m·K) c (for mortars intended to be used in elements subject to thermal requirements) According to BS EN 1745:2002,Table A.12
2.4.2.10	Reaction to Fire (Class) according to clause (5.2.2) of BS EN 998-1:2016 standard, if applicable
2.4.3.11	Durability if applicable to be evaluated as per clause [5.2.3] of BS EN 998-1:2016 standard

- 2.4.3 Independent test shall only be conducted if the result of the applicable in-plant test shows satisfactory results. DCLD-PCAS may opt to accept available valid test reports conducted by an approved DCLD-PCAS independent laboratory within one year from the date of the initial assessment, in line with the internal quality control testing plan of the factory. In such case, the testing of that particular parameter(s) shall be waived accordingly.
- If the result of the test conducted by the DCLD-PCAS approved independent testing laboratory shows non-2.4.4 conformance to the specified requirements, the provision for rejection specified in the standard shall apply. The retest shall be carried out on the reference sample kept by the manufacturer or on new samples collected by the authorized auditor on which full testing shall be carried out ,if necessary.

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 6 of 9

~3 8 v ~7	Organization/Unit:	إدارة مختبر دبي المركزي Dubai Central Laboratory Department	الوحدة التنظيمية:	
GOVERNMENT OF DUBAI	Document Title:	Specific Rules For Certification of Rendering and Plastering Mortar (as per BS EN 998-1:2016) Through Factory Assessment	عنوان الوثيقة:	بلدية دبي
	Doc Ref.	DM-DCLD-RD-DP21-2193 (IC)	رقم الوثيقة:	

- 2.4.5 If the retest passed, the initial product assessment is considered conforming to product specification. If not, the manufacturer will be advised to take corrective action.
- 2.4.6 Only after reassessment and subsequent product compliance shall the certification proceed with the granting of the DCL Certification.

3. GRANTING OF THE DCL CERTIFICATION

3.1 CONDITIONS FOR GRANTING THE DCL PRODUCT CONFORMITY CERTIFICATE

- 3.1.1 When the results of the factory audit (clause 2.3) and product evaluation (clause 2.4) show conformity to the requirements specified in the general rule and specific rule, the Certificate of Conformity and authorization to use the DCL Conformity Mark shall be issued to the client for the type(s)/model(s)/brand(s) of the product covered by the assessment.
- 3.1.2 The client shall agree with DCLD-PCAS for the preparation and implementation of a product quality assurance plan / mechanism to ensure continuing compliance with the Standard Specifications and the requirements of this certification scheme. It shall consist of (1) an internal product quality assurance plan, and (2) an independent testing plan.

3.1.3 Internal product quality assurance plan

The client shall have an internal product quality assurance plan giving details of the tests to be carried out at the factory. This will include as a minimum, the following details: (1) location of sampling; (2) frequency of sampling; (3) quantities of samples; (4) tests to be carried out; (5) results acceptance criteria; and (6) responsible person to carry out the activity

The plan shall take into consideration the production process, the volume of production, the criticality of the test to be specified, and other relevant factors

3.1.4 Independent testing plan

The client shall agree to an independent testing plan to be carried out on samples which are collected in accordance with DM-DCLD-RD-DP21-2096 (IC) – Surveillance of Certified Clients under the Factory Assessment Scheme, and implemented by DCLD-PCAS.

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 7 of 9



3.2 ISSUANCE OF DCL CERTIFICATE OF CONFORMITY

If the conditions mentioned in clause 3.1 above have been complied, the client shall be issued a DCL Certificate of Conformity and a Scope of Certification that covers the type(s) and size of the products that are certified and will be authorized to use the DCL Conformity Mark on the certified products.

3.3 RESPONSIBILITIES OF THE CERTIFIED CLIENT

- 3.3.1 The client shall ensure that his product, for which a certificate of conformity has been issued, conforms at all times to the requirements of the General Rule and Specific Rules and shall maintain to the satisfaction of DCLD-PCAS, a system of quality control including inspection and testing.
- 3.3.2 The client shall give the duly authorized auditor(s), access during working hours, without prior notification, to the premises of the factory where certified product is manufactured, for the purpose of evaluating the materials, production processes, finished products, quality assurance facilities, records and others in accordance with the requirements of the scheme.
- 3.3.3 The client shall inform DCLD-PCAS in writing of any change of management, transfer of plant site, modification in the product, manufacturing process or factory's quality management system.
- 3.3.4 Upon transfer of plant site, the certificate of conformity shall be deemed valid only after factory and product audit at the new site has been satisfactorily completed.
- 3.3.5 Any infraction stated in the terms and conditions of the certification scheme and the use of DCL Conformity Mark shall constitute sufficient grounds for suspension, withdrawal and termination of certification in accordance with DM-DCLD-IMS-RD-07.
- 3.3.6 Any dispute that may arise in connection with the Terms and Conditions of the certification scheme shall be settled in accordance with DM-DCLD-IMS-RD-08 Appeals, Disputes, and Complaints Procedure.
- 3.3.7 The client shall pay all applicable fees related to the certification process.
- 3.4 USE OF THE DCL CONFORMITY MARK
- 3.4.1 The design and use of the DCL Conformity Mark shall be in accordance with the Terms and Conditions for the Use of the DCL Conformity Mark, DM-DCLD-IMS-RD-13

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 8 of 9

GOVERNMENT OF DUBAI	Organization/Unit:	إدارة مختبر دبي المركزي Dubai Central Laboratory Department	الوحدة التنظيمية:	
	Document Title:	Specific Rules For Certification of Rendering and Plastering Mortar (as per BS EN 998-1:2016) Through Factory Assessment	عنوان الوثيقة:	بادية دبي
	Doc Ref.	DM-DCLD-RD-DP21-2193 (IC)	رقم الوثيقة:	

- 3.4.2 The client shall submit a product-marking proposal for approval by DCLD-PCAS. The proposal shall include drawings and/or diagrams showing the location and size of the marking for each size of the product/product container, where applicable
- 3.4.3 The Certificate of Conformity and the authorization to use the DCL Conformity Mark is non-transferable.

4. SURVEILLANCE

- 4.1 DCLD-PCAS or their approved CAB shall carry out periodic surveillance to ensure consistent compliance with the requirements of this certification scheme as per DM-DCLD-RD-DP21-2096 (IC) Surveillance of Certified Clients under the Factory Assessment Scheme.
- 4.2 Testing as part of the surveillance shall be in accordance with the Independent Testing Plan (clause 3.1.4) that has been agreed between DCLD-PCAS and the client.

5. FEE SCHEDULE

- The client shall pay the applicable fees and charges related to the granting of the certificate of conformity and the authorization to use the DCL Conformity Mark based on DCL Official Fee Structure, DM-DCLD-RD-DP21-2074 (IC).
- 5.2 The fees for this certification scheme shall include but not limited to the following
 - 5.2.1 Application Fee
 - 5.2.2 Initial Assessment Fee
 - 5.2.3 Certification Fee
 - 5.2.4 Marking Fee
 - 5.2.5 Surveillance Fee
 - 5.2.6 Annual Renewal Fee
 - 5.2.7 Testing Fee
 - 5.2.8 Outsource Activity Fee , where applicable

Approved by HOU	Authorized by PCASM
Date of Issue : 04/08/2020	Rev. No. : 06
درجة السرية / Level of Confidentiality : عام / General	Page 9 of 9