

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

SIKA UAE L.L.C

Plot No 61-0 DM No. 533-279, Saih Shuaib 4, Dubai Industrial City, P.O. Box 126212, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL17020432
Valid Until: 25/02/2022



Current Issue Date: 17/03/2021
Original Issue Date: 26/02/2017



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

Certificate Issued To:

SIKA UAE L.L.C

Plot No 61-0 DM No. 533-279, Saih Shuaib 4,

Dubai Industrial City (DIC), P.O. Box 126212, Dubai, UAE

Applicable Standard Specification:

2017 Al Sa'fat – Dubai Green Building Evaluation System

Applicable Specific Rules:

DM-DCLD-RD-DP21-2180-(IC) Specific Rules for FA
Certification of Low Emitting Materials as per Al Sa'fat -
Dubai Green Building Evaluation System

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Two pack reactive performance coatings for specific end use such as floors, (Product Sub-category: 10)	Sika Seal-105 (A+B)	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 140 g/l) (For interior applications) <u>These products are produced in SIKA - UAE</u>
		SikaTop Seal-107 (A+B)	
		Sikalastic-152 AE (A+B)	
		Sikafloor-20 PurCem AE (A+B)	
		Sikafloor-21 PurCem AE (A+B)	
		Sikafloor-29 PurCem AE (A+B)	
		Sikafloor-31 PurCem AE (A+B)	
		Sikagard-65 WN	
		Sikafloor®-220 W Conductive*	
		Sikafloor-324	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For interior applications) <u>These products are now being produced in SIKA - UAE</u>
		Sikafloor-3240	
		Sikafloor-264	
		Sikafloor-264 SG	
		Sikafloor-263 SL	
		Sikagard-62	
		Sikalastic-702*	
		Sikalastic-8850*	
		Sikafloor®-304 W*	
		Sikafloor®-305 W*	
		Sikafloor®-305 W ESD*	
		Sikafloor®-262 AS N*	
		Sikafloor-700*	
		Sikafloor-190 Screed*	
		Sikagard PW*	
		Sikafloor Terrazzo SA*	
		Poxitar-LS	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For interior applications) <u>These products are produced in SIKA Gulf – Bahrain</u>
		Sikafloor-190 Screed	
		Sikafloor-2430	
		Sikafloor-2430 SG	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

	Two pack reactive performance coatings for specific end use such as floors, (Product Sub-category: 10)	Sikafloor-262 AS N	<p>(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For interior applications) <u>These products are produced in SIKA Gulf - Bahrain</u></p>
		Sikafloor-263 SL	
		Sikafloor-264	
		Sikafloor-264 SG	
		Sikafloor-264 TD	
		Sikafloor-304 W	
		Sikafloor-305 W	
		Sikafloor-3240	
		Sikafloor-325	
		Sikafloor-326	
		Sikafloor-375 SG	
		Sikafloor-81 EpoCem	
		Sikafloor-82 EpoCem	
		Sikafloor-83 Epocem	
		Sikafloor-LM	
		Sikafloor-Terrazo SA	
		Sikagard-320 EPS	
		Sikagard-PW	
		Sikalastic-851	
		Sikalastic-851 R	
		Sikalastic-8800	
		Sika Permacor-2230 (VHS)	<p>(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For Exterior applications) SRI: CLASS 1 for White color – See Note #3 <u>These products are produced in SIKA Gulf - Bahrain</u></p>
		Sikafloor-359 SG	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

2	Two pack reactive performance coatings for specific end use such as floors, (Product Sub-category: 10) Roof Coating/ Coating Applied to Hardscapes*	Sikalastic-701*	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) SRI: CLASS 1 for White color – See Note #3 (For exterior applications) <u>These products are produced in SIKA - UAE</u>
		Sikafloor-359 BH*	
3	Binding Primers (Product Sub-category: 8)	SikaBond DV	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 30 g/l) (For interior/Exterior applications) <u>These products are produced in SIKA Gulf - Bahrain</u>
		SikaTop Armatec-110 EpoCem	
		Sikafloor-CureHard-24	
		SikaLatex	
		Sika Latex*	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 30 g/l) (For interior/exterior applications) <u>These products are produced in SIKA - UAE</u>
		SikaBond DV*	
		SikaTop Armatec-110 EpoCem*	
		Sikafloor PS	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 750 g/l) (For interior/Exterior applications) <u>This product is produced in SIKA Gulf - Bahrain</u>
		Sikagard-700 S	
		Sikadur PF	
		Sikagard-700 S*	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 750 g/l) (For interior/exterior applications) <u>These products are produced in SIKA - UAE</u>
		Sikadur PF*	
		Sikafloor PS*	
		SikaBit P-12 AE*	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

4	Primers (Product Sub-category: 7)	Sika Astar	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 30 g/l) (For interior/Exterior applications) <u>These products are produced in SIKa Gulf – Bahrain</u>
		Sikagard-552 W Aquaprimer (G)	
		Sikagard-720 EpoCem	
		Sikagard-Putty	
		Sika Concrete Primer	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 350 g/l) (For interior/Exterior applications) <u>These products are produced in SIKa Gulf - Bahrain</u>
		Sikafloor-161	
		Sikafloor-161 G	
		Sikagard-705 L	
		Sikafloor-161	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 350 g/l) (For interior applications) <u>These products are produced in SIKa - UAE</u>
		Sikafloor-161 G	
5	Sealants*	Sikaseal-410 PG*	ARCHITECTURAL (AL SA'FAT-DGBES VOC limit is max. 250 g/l) (For interior/exterior applications) <u>These products are produced in SIKa - UAE</u>
		Sikaseal-411 GG*	
6	Adhesives, Ceramic tiles adhesive	SikaCeram-51	VOC (AL SA'FAT-DGBES limit is max 65 g/l) <u>These products are produced in SIKa – UAE</u>
		SikaCeram-101	
		SikaCeram-117	
		SikaCeram-118	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

	Adhesives, Ceramic tiles adhesive	SikaCeram-201	VOC (AL SA'FAT-DGBES limit is max 65 g/l) These products are produced in SIKA - UAE
		SikaCeram-201 LM (A+B)	
		SikaCeram-216	
		SikaCeram-217	
		SikaCeram-255 StarFlex LD-AE	
		SikaCeram-500 TG AE	
		SikaCeram-502 LM (A+B)	
		SikaCeram-502 TG AE	
		SikaCeram-503 TG*	
		SikaCeram-801 RTG*	
		SikaCeram RTG	VOC (AL SA'FAT-DGBES limit is max 65 g/l) <u>These products are produced in SIKA Gulf - Bahrain</u>
		Sikadur-43 TA	
7	Adhesives, Special Purpose Contact Adhesive	Sikadur-30 LP	VOC (AL SA'FAT-DGBES limit is max 250 g/l) <u>These products are produced in SIKA Gulf – Bahrain</u>
		Sikadur-330	
		Sikadur-300	
		Sikadur-31 CF Slow	
		Sikadur-31 DW	
		Sikadur-31 SBA (h) S-02	
		Sikadur-31 SBA 30-50	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

	Adhesives, Special Purpose Contact Adhesive	Sikadur-31 SBA S-03	VOC (AL SA'FAT-DGBES limit is max 250 g/l) These products are produced in SIKA Gulf - Bahrain
		Sikadur-31 SBA S-04	
		Sikadur-31 SBA S-08	
		Sikadur-32 Hi-Mod	
		Sikadur-32 LP	
		Sikadur-330	
		Sikadur-41 CF Slow	
		Sikadur-31 SBA S-02 MY*	
		SikaProof Adhesive-01*	VOC (AL SA'FAT-DGBES limit is max 250 g/l) <u>These products are produced in SIKA - UAE</u>
		Sikadur-31 CF Slow*	
		Sikadur-41 CF Slow*	
8	Adhesives, Sheet Applied Rubber Lining Operations*	Sika® Bitumen Adhesive-270*	VOC (AL SA'FAT-DGBES limit is max 850 g/l) <u>This product is produced in SIKA - UAE</u>
9	One-pack Performance Coating (Product Sub-category 9)	Sikagard-550 W Elastic (G)	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 140 g/l) (For Exterior applications) SRI: CLASS 1 LRV: Class 1 for White color – See Note #3 <u>These products are produced in SIKA Gulf - Bahrain</u>
		Sikagard-690 WHD	
		SikaFill-100 (BH)	
		Sikalastic-560 GCC	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL17020432

One-pack Performance Coating (Product Sub-category 9)	Igasol Emulsion BA	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 140 g/l) (For Interior applications) <u>These products are produced in SIKA Gulf - Bahrain</u>
	Igasol Emulsion BA-10	
	Igasol Emulsion BA-6510	
	Sika Bitumen AE	
	Sikalastic WR	
	Sikalastic-601 BC	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For Interior applications) <u>The product is produced in SIKA Gulf - Bahrain</u>
	Sikalastic-311 (AE)	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For Interior applications) <u>The product is produced in SIKA - UAE</u>
	Sika Monotop-109 Waterproofing AE*	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 140 g/l) (For Interior applications) <u>These products are produced in SIKA - UAE</u>
	Igasol Emulsion BA*	
	Igasol Emulsion BA-10*	
	Igasol Emulsion BA-6510*	
	Sika Bitumen AE*	
	Sikalastic-445	(Solvent Base) (AL SA'FAT-DGBES VOC limit is max. 500 g/l) (For Exterior applications) SRI: CLASS 1 LRV: Class 1 for White color – See Note #3 <u>These products are produced in SIKA Gulf - Bahrain</u>
	Sikalastic-621 TC	
	Sikagard-680 SG	
	Sikalastic-614	



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL17020432**

10	One-pack Performance Coating (Product Sub-category 9) Coatings (other than paint) for exterior/exposed wall application*	Sikagard-520 W*	(Water Base) (AL SA'FAT-DGBES VOC limit is max. 140 g/l) (For Exterior applications) LRV: Class 1 for White color – See Note #3 <u>These products are produced in Sika Gulf - Bahrain</u>
----	---	-----------------	---

With * are newly added products

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE2: The above product shall bear the DCL Conformity Mark.

NOTE3: For colors/types not covered by the Scope, SRI/LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the 2017 Al Sa'fat –Dubai Green Building Evaluation System.

SRI Class 1 (≥ 78) – “Can be Used in 75 - 100% of surface to be coated – Sloped or Flat Roof”

SRI Class 2 ($29 < 78$) - “Can be Used in 75 - 100% of surface to be coated – Sloped Roof”

SRI Class 3 (< 29 or untested) – “Can be Used in 0 – 25% of surface to be coated – Sloped or Flat Roof “

LRV Class 1 (≥ 45) – “Can be used in 75-100% of surface to be /painted/coated”

LRV Class 2 (< 45) – “Can be used in 0-25% of surface to be painted/coated”

Original Issue Date: 26 February 2017

Current Issue Date: 17 March 2021

Valid Until: 25 February 2022

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department