



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

CAPAROL PAINTS LLC

Saih Shuaib-4 Dubai Industrial City, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: CL17020465 Valid Until: 06/06/2021



Current Issue Date: 07/06/2020 Original Issue Date: 07/06/2017



DM-DCLD-F-IC-2031 Rev 17

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION Rev 01 FOR CERTIFICATE NO. CL17020465

Certificate Issued To CAPAROL PAINTS LLC

Saih Shuaib-4, Dubai Industrial City, Dubai, UAE

Applicable Standard Specification: 2017 Al Sa'fat - Dubai Green Building Evaluation

System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180 (IC) Specific Rules for

FA Certification of Low Emitting Materials as per 2017 Al Sa'fat - Dubai Green Building Evaluation

System

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
		AirPurify	
		CapaCare	Water Base Paint for Interior Application Only:
	Interior Matt Walls	CapaMat	VOC (Al Sa'fat-DGBES limit is max.30 g/l)
1	and Ceilings Paint (Gloss < 25 @ 60°) (sub category 1)	CapaPlus	Heavy metals: Cadmium and Chromium VI
		CleanStar	(Al Sa'fat-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead
		CapaFlat	(Al Sa'fat-DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
		Optima Interior *	
			Water Base Paint for Interior Application
		CleanStar	Only:
	Interior glossy walls and ceilings		VOC (Al Sa'fat-DGBES limit is max.100 g/l)
2	paints (Gloss > 25		Heavy metals: Cadmium and Chromium VI
	@60°)		(Al Sa'fat-DGBES limit < 500 mg/Kg),
	(sub category 2)	Amphibolin	Arsenic, Mercury and Lead
			(Al Sa'fat-DGBES limit <100 mg/Kg)
			Formaldehyde ≤ 10 mg/kg





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION Rev 01 FOR CERTIFICATE NO. CL17020465

		CapaPutz Primer	Water based Primer for
	Primers (sub category 7)	CapaStucco	Interior/Exterior Applications:
		FlexoPrime	VOC (Al Sa'fat-DGBES limit is max.30 g/l)
3		StonePrime	Heavy metals:Cadmium & Chromium VI
		CapaAcryl Primer	(Al Sa'fat-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead
		CapaFilex	(Al Sa'fat-DGBES limit <100 mg/Kg)
		CapaPrime	Formaldehyde ≤ 10 mg/kg
			Water Base Paint for Interior
	Decorative Effects Coatings (sub category 12)	Metallocryl Interior	Application Only:
			VOC (Al Sa'fat-DGBES limit is
			max 200 g/l)
			Heavy metals: Cadmium & Chromium VI
4		Makhmalia	(Al Sa'fat-DGBES limit < 500 mg/Kg),
			Arsenic, Mercury and Lead
			(ALC 15 + DCDEC 1: 1: 400 - 414)
			(Al Sa'fat-DGBES limit <100 mg/Kg)
			Formaldehyde ≤ 10 mg/kg
		FlexoTop	
		Amphibolin]
		CapaUltra Matt	Water Base Paint for Exterior
		CleanStar	Application:
		CapaShield	
		CapaTex (Textured coatings)	VOC (Al Sa'fat-DGBES limit is max 40 g/l)
_	Exterior Walls of	TopTex (Textured coatings)	Heavy metals: Cadmium & Chromium VI
5	Sub category 3)	CapaGrain (Textured coatings)	(Al Sa'fat-DGBES limit < 500 mg/Kg),
		CapaStructure (Textured coatings)	- Arsenic, Mercury and Lead - (Al Sa'fat-DGBES limit <100 mg/Kg)
		FlexoGuard	- (AI Sa fat-DGBES limit < 100 mg/kg) - Formaldehyde ≤ 10 mg/kg
		StructurePutz (Textured coatings)	LRV Class: Class 1
		FlexoShield	(see Note 3)
		CapaSpraytex (Textured coatings)	(See Note 3)
		FlexoPutz	1





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION Rev 01 FOR CERTIFICATE NO. CL17020465

		Flexotex	1020-100
		CapaStone NanoClear	1
		Ceratile	
		Ceratone	
		Granito	1
		Eurostone	1
		CapaStone Basecoat	1
		Decocoat	
		Optima Exterior *	1
		Capacoat Exterior *	
		Nano 360 *	1
		0 1 - 1	Solvent Base Coating for
		Capalac Enamel	Interior/Exterior Applications:
6	One -pack Performance Coatings (sub category 9)	CapaTopacryl	VOC (Al Sa'fat-DGBES limit is max 500 g/l) LRV Class: Class 2 (see Note 3) (Average LRV Class 2 < 45)
			LRV Class: Class 1 (see Note 3)
		CapaMark	(Average LRV Class 1 ≥ 45)
		СараЕроТор	
		СараЕроТех	
	Two -pack Reactive	CapaThane	Solvent Base/Solvent Free Coating for Exterior/Interior Application:
	Performance	CapaEpo HB undercoat	
7	Coatings for	DisboPOX 110 SB	VOC (Al Sa'fat-DGBES limit is
	::: :	DisboPOX 210 SF	max 500 g/l)
	specific end use	2.000. 07. 220 0.	
	such as floors	DisboPOX 230 SF	LRV Class: Class 1 (see Note 3)
	-		LRV Class: Class 1 (see Note 3) (Average LRV Class 1 ≥ 45)
	such as floors	DisboPOX 230 SF	
	such as floors	DisboPOX 230 SF DIsboPUR 630 PU	(Average LRV Class 1 ≥ 45)
	such as floors	DisboPOX 230 SF DIsboPUR 630 PU DisboPOX 231 SF *	(Average LRV Class 1 ≥ 45)
8	such as floors (sub category 10)	DisboPOX 230 SF DIsboPUR 630 PU DisboPOX 231 SF * Capalac red oxide primer	(Average LRV Class 1 ≥ 45) Solvent Base Primer for Interior/Exterior





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION Rev 01 FOR CERTIFICATE NO. CL17020465

Capaseal SB	
Disboxan 485	

NOTE 1:This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark.

NOTE 3: For colors/types not covered by the Scope, LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-GBRS.

- LRV Class 1 (≥45) "Can be used in 75-100% of surface to be /painted/coated"
- LRV Class 2 (<45 or untested) "Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1".

NOTE 4: " * " Additional New Products

NOTE 5: This supersedes the scope of certification issued on 07 June 2020

Original Issue Date: 07 June 2017

Current Issue Date: 22 November 2020

Valid Until: 06 June 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department