



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL18020596

		CONTEX SILOXANE ACRYLIC PRIMER 06300	Arsenic, Mercury and Lead (Al Sa'fat DGBES limit <100 mg/Kg)
		HEMPEL'S FAST DRY PRIMER 131ME	
		HEMPALIN PRIMER 12050	
		MAESTRO ALKYD UNDERCOAT 22460	
3	Interior matt walls and ceilings paint (Gloss < 25@60°) (Category 1)	MAESTRO DECOR EMULSION 58250	Water Base Paint for Interior Applications: VOC (Al Sa'fat DGBES limit is max 30 g/l) Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
		MAESTRO MATT EMULSION 594ME	
		MAESTRO PRO EMULSION 595ME	
		MAESTRO SILK EMULSION 58331	
		TOPAZ MATT EMULSION 588ME	
		TOPAZ SILK EMULSION 589ME	
		TOPAZ ZERO MATT 58803	
		TOPAZ ZERO MATT WITH SILVER IONS 58801	
		TOPAZ ZERO SILK 58903	
		TOPAZ ZERO SILK WITH SILVER IONS 58901	
		HEMPEL'S MOULDEX 58520	
		TOPAZ SG EMULSION 587ME	
		TOPAZ ZERO SG 58703	
4	Interior glossy walls and Ceilings paint(Gloss > 25 @60 °) (Category 2)	TOPAZ GLOSS EMULSION 580ME	Water Base Paint for Interior Applications: VOC (Al Sa'fat DGBES limit is max 100 g/l) Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat DGBES limit <100 mg/Kg) Formaldehyde ≤ 10 mg/kg
5	Two -pack Reactive Performance Coatings (Category 10)	HEMPADUR MULTI STRENGTH 35530	Solvent Base Coating for Interior Application: VOC (Al Sa'fat DGBES limit is max 500 g/l)
		HEMPADUR 35560	
		HEMPATHANE ENAMEL 55100	
		HEMPADUR FAST DRY 15560	



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL18020596

		HEMPADUR FAST DRY 17410	
		HEMPADUR SEALER 05990	
		HEMPADUR HI-BUILD 45200	
		HEMPADUR 35600	
		HEMPADUR ZINC 17360	
		HEMPADUR AVANTGUARD 750 1736G	
		STRATA HT 35590	
		STRATA MT 45520	
		STRATA SEALER 05920	
		STRATA PRIMER SF 25350	
		STRATA EPOXY WALL FILLER 350ME	
		STRATA EPOXY FLOOR FILLER 35270	
		STRATA LT 45120	
		STRATA EPOXY ANTI-MICROBIAL HT 35592	
		STRATA PU TOP 55160	
		STRATA SCREED S 35961	
		STRATA SCREED R 35962	
		STRATA EPOXY SL 2000 35834	
		STRATA EPOXY SL 5000 3583A	
		HEMPEL'S EPOXY TEXTURE 45450	
		HEMPATHANE TOPCOAT 55210	Solvent Base Coating for Interior / Exterior Application: VOC (Al Sa'fat DGBES limit is max 500 g/l) For White colors. LRV: Class 1 SRI: Class 1 (See Note 3)
		HEMPATHANE TOPCOAT 55610	
		STRATA EPOXY WB 48560	Water Base Coating for Interior Application: VOC (Al Sa'fat DGBES limit is max 140 g/l)
6	Exterior walls for mineral substrates (Category 3)	CONTEX EM 58600	Water Base for Exterior Applications: VOC (Al Sa'fat DGBES limit is max 40 g/l) Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead
		CONTEX THERMOGUARD 58620	
		CONTEX TOP COAT MATT 48610	
		CONTEX TOPCAOT SG 48630	
		CONTEX TOPCOAT SILK 48620	
		CASA EXTERNAL WASH 681ME	
		TOPAZ COARSE TEXTURE 58870	



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL18020596

		<p>TOPAZ FINE TEXTURE 58850</p> <p>TOPAZ MEDIUM TEXTURE 58860</p> <p>CONTEX FINE TEXTURE 58740</p> <p>CASA DECOR 582AE</p> <p>CONTEX TEX MEDIUM 58742</p> <p>CASA CRAFT TEX 586ME</p> <p>CASA STONE TEX (HB) 585ME</p> <p>CASA STONE TEX (HS) 582ME</p> <p>CASA STONE TEX (STD) 583ME</p> <p>MAESTRO SMOOTH TEXTURE 48740</p> <p>TOPAZ SPATTER FINISH 38860</p> <p>HEMPAROOOF 596ME</p>	<p>(Al Sa'fat DGBES limit <100 mg/Kg)</p> <p>Formaldehyde \leq 10 mg/kg</p> <p>For White colors. LRV: Class 1 SRI: Class 1 (See Note 3)</p>
7	<p>One -pack Performance Coatings (Category 9)</p>	<p>STRATA WB AIRFIELD AND ROAD MARKING 28101</p>	<p>Water Base for Interior / Exterior Applications: VOC (Al Sa'fat DGBES limit is max 140 g/l)</p> <p>For White colors. SRI: Class 1 - See Note #3</p>
		<p>HEMPAFIRE OPTIMA 500 48880</p>	<p>Water Base for Interior Applications: VOC (Al Sa'fat DGBES limit is max 140 g/l)</p>
8	<p>Interior/Exterior trim and Cladding paints for wood and metal (Category 4)</p>	<p>HEMPADUR MASTIC 45881/45880</p>	<p>Solvent Base for Interior/Exterior Applications: VOC (Al Sa'fat DGBES limit is max 300 g/l)</p> <p>Heavy metals: Cadmium and Chromium VI (Al Sa'fat DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat DGBES limit <100 mg/Kg)</p> <p>Formaldehyde \leq 10 mg/kg</p> <p>For White colors. LRV: Class 1 SRI: Class 1 (See Note 3)</p>
		<p>HEMPAPRIME MULTI 500 45950</p>	



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL18020596

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark.

NOTE 3: For colors/types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-AL SA'FAT DGBES.

- SRI Class 1 (≥ 78) – “Can be Used in 75 - 100% of surface to be coated – Sloped or Flat Roof”
- SRI Class 2 ($29 < 78$) - “Can be Used in 75 - 100% of surface to be coated – Sloped Roof”
- SRI Class 3 (< 29 or untested) – “Can be Used in 0 – 25% of surface to be coated – Sloped or Flat Roof provided the remaining area is Class 1 or 2”
- LRV Class 1 (≥ 45) – “Can be used in 75-100% of surface to be /painted/coated”
- LRV Class 2 (< 45 or untested) – “Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1”.

Original Issue Date: 11 June 2018

Current Issue Date: 11 June 2020

Valid Until : 10 June 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department