



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

CONMIX LIMITED CO. (LLC)

Dubai Industrial City, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department Dubai Municipality



Certificate No: CL18020619 Valid Until: 23/07/2021



Current Issue Date: 24/07/2020 Original Issue Date: 24/07/2018



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.

This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020619

Certificate Issued To CONMIX LIMITED CO. LLC

Dubai Industrial City, Dubai, UAE

Applicable Standard Specification:2017 Al Sa'fat Dubai Green Building Evaluation

System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180-(IC) Specific Rules for

FA Certification of Low Emitting Materials as per Al Sa'fat – Dubai Green Building Evaluation System.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
		ConDure PVA Primer	Water Base Paint for Interior Application
		ConDure Stucco Filler	
		PinTura Cenomast Matt	VOC (Al Sa'fat DGBES limit is
		PinTura Cenomast Hygiene	max. 30 g/l)
	Interior Matt Walls	Conmix Spray Plaster – Base Coat	Heavy metals: Cadmium and
1	and Ceiling Paints	Conmix Spray Plaster – Fine	Chromium (Al Sa'fat DGBES limit is <
	(Gloss <25 @ 60°)	Conmix Spray Plaster – Coarse	500 mg/Kg), Arsenic, Mercury and
		Conmix Spray Plaster – Medium	Lead (Al Sa'fat DGBES limit is <100 mg/Kg)
		PinTura Matt Emulsion	
			Formaldehyde (Al Sa'fat DGBES limit
		PinTura Plastic Emulsion	is <u><</u> 10 mg/kg)
		PinTura Super Matt Emulsion	is <u><</u> 10 mg/ kg/
		D' T C C'II	W. to a D. o D. o t
		PinTura Cenomast Silk	Water Base Paint for Interior Application
			VOC (Al Sa'fat DGBES limit is
		PinTura Cenomast Gloss	max. 100 g/l)
	Interior Glossy Walls		Heavy metals: Cadmium and
2	and Ceiling Paints (Gloss >25 @ 60°)	PinTura Cenomast Stain Resistant	Chromium (Al Sa'fat DGBES limit
		Emulsion	·
		PinTura Cenomast Hygiene Silk	is < 500 mg/Kg), Arsenic, Mercury
		PinTura Cenomast Semigloss	and Lead (Al Sa'fat DGBES limit is <100 mg/Kg)
		PinTura Silk Emulsion	
			Formaldehyde (Al Sa'fat DGBES limit
			is ≤ 10 mg/kg)





		PinTura Tyroshield Matt	
		PinTura Tyroshield Matt Colourlast	
		PinTura Tyroshield Silk Colourlast	
		PinTura Tyroshield Ultra Flex	
		ConTxtra Monodeco	
		ConTxtra Heritagedeco	
		ConTxtra Classicdeco	Water Base Paint for Exterior Application
		ConTxtra Glintex	
		ConTxtra Elegante	VOC (Al Sa'fat DGBES limit is
		Moyashield Uflex	
		PinTura Tyroshield Silk	max. 40 g/l)
		PinTura Tyroshield Gloss	Heavy metals: Cadmium and
		PinTura Acrylic Matt Emulsion	Chromium (Al Sa'fat DGBES limit
	Exterior Walls of	ConTxtra Monodeco Fine	is < 500 mg/Kg), Arsenic,
		ConTxtra Heritagedeco Medium	Mercury and Lead (Al Sa'fat DGBES
		ConTxtra Heavydeco	limit is <100 mg/Kg)
2		ConTxtra Heavydeco Medium	Formaldehyde (Al Sa'fat DGBES limit
3	Mineral Substrate	ConTxtra Heavydeco Fine	is <u><</u> 10 mg/kg)
		ConTxtra Minitex	
		ConTxtra FineTex	DEIGE COLOR
		ConTxtra Rolldeco	BEIGE COLOR SRI Class 2 (29 < 78) - can be used in
		ConTxtra Elegante Medium	75-100% surfaced to be coated -
		ConTxtra Armotex	Sloped Roof
		ConTxtra Armotex Medium	·
		ConTxtra Tyro Compound	LRV Class 1 (=> 45) - can be used in
		MoyaShield ACC Putty	75-100% surfaced to be
		MoyaShield ACC	coated/painted
		Uflex Primer No. 1	(SEE NOTE 3)
		MoyaShield Uflex White	
		MoyaShield Uflex HR	
		Moyashield BE	
		Moyashield RBE	
		Moyashield PU	
		PinTura Tyroshield ColourExtreme	





		Silk	
		Pintura Tyroshield ColourExtreme	
		Matt	
		DecoStone Smooth	
		DecoStone Medium	
		DecoStone Coarse	
		DecoStone Basecoat	
		ConDure StoneGuard Nano Clear	
		ConDure Universal Primer	Water Base
		ConDure Stucco Filler (Acrylic)	for Exterior Application
4	Primer	MoyaShield Primer	
		Uflex Primer No. 2	VOC (Al Sa'fat DGBES limit is
		ConDure Stone Primer	max. 30 g/l)
		ConDure Alkali Resistant Primer	
		ConDure Siloxane Primer	Water Base
5	Binding Primer	ConDure Penetrating Sealer	for Interior/Exterior Application
		Conmix ConPutty	VOC (Al Sa'fat DGBES limit is max. 30 g/l)
		ConDure Acrylic Penetrating Primer	111ax. 30 g/1)
		ConLite Hi-Gloss Enamel	
	One Pack Performance Coating	ConGuard Acrylic Topcoat	Solvent Base for Interior and
		ConGuard Acrylic Topcoat Matt	Exterior Application
		ConLite Metal Primer Red Oxide	
		ConLite Synthetic Undercoat	VOC (Al Sa'fat DGBES limit is
6		ConLite Semigloss Enamel	max. 500 g/l)
		ConLite Matt Enamel	
		MoyaShield Uflex 100 White	Water Base for Interior and Exterior
		Moyasineid Offex 100 White	Application
		ReCon AP	VOC (Al Sa'fat DGBES limit is
			max. 140 g/l)
7	Two Pack Reactive Performance Coating for Specific End such as floor	Moyaproof WS2	Water Base for Interior and Exterior
		Moyaproof WS2 M	Application
		MoyaProof HF	VOC (Al Sa'fat DGBES limit is max. 140 g/l)
		ConFloor PU Topcoat	Solvent Base for Exterior
L	<u> </u>	'	1





Resigard PU - Pigmented	Application
ConGuard Tyrothane Semi Gloss	
ConGuard Tyrothane Gloss	VOC (Al Sa'fat DGBES limit is max.
ConGuard Tyrothane Clear	500 g/l)
ConGuard Tyrothane Clear Matt (M)	
ConFloor Epoxy Topcoat	
ConGuard Tyrothane Matt	
Resigard NT	
Resigard EC	
Resigard PU - CP	
Resigard HP (2K)	
Resigard Primer SF	
Resigard Primer SB	
Recon Zinc	
ConFloor Epoxy Topcoat SB	Solvent Base for Interior Application
ConFloor SB Epoxy Primer	VOC (ALC-YELL DEDEC limits in more
ConFloor SF Epoxy Primer	VOC (Al Sa'fat DGBES limit is max. 500 g/l)
ResiGard HB	500 g/1)
Resigard NC	
Resigard HP	
ResiGard RS5	
ConGuard Epoxy Sealer	
ConGuard Epoxy Topcoat	
ConGuard Zinc Phosphate Primer	
ConGuard SF Epoxy Primer	
ConGuard SF Epoxy Topcoat	
ResiGard Primer Pigmented	
ConGuard Epoxy Primer White	
ConGuard Epoxy Tyro Compound	Solvent Base for Interior and Exterior Application VOC (AI Sa'fat DGBES limit is max. 500 g/l)





8	Multi Colored Coating	ResiGard Primer WB	Water Base for Interior Application
		ResiGard EWD	VOC (Al Sa'fat DGBES limit is
		ResiGard EC WB	max. 100 g/l)
9	Sealants Others	SealXtra PU	
		SealXtra LM	VOC (Al Sa'fat DGBES limit is
		SealXtra PS	max. 420 g/l)
		SealXtra PUFR	
10	Sealant Primer Others	SealXtra Primer	Solvent Based VOC (Al Sa'fat DGBES limit is max. 750 g/l)
		Conmix Insubond	Premix Cementitious Powder
11	Drywall & Panel Adhesive	Conmix Insubond (M)	VOC (Al Sa'fat DGBES limit is max. 50 g/l)
		Tilex EGWB	
		Tilex LM (Two Component)	Solvent Free Epoxy Adhesive
		Tilex EG	VOC (Al Sa'fat DGBES limit is
	Ceramic Tile Adhesive	Tilex EP	max. 65 g/l)
		Water Resistant Tile Adhesive	
		C500 (Grey)	
		Water Resistant Tile Adhesive	
		C500 (White)	
		Water Resistant Tile Adhesive	
		C800	
40		Universal Tile Glue – UTG	
12		Universal Tile Glue – UTG (White)	Cement Based Premix Cementitious
		Conmix Tile Adhesive – CTA	Powder
		Conmix Tile Adhesive – CTA (White)	VOC (Al Sa'fat DGBES limit is
		Thick Bed Mortar- THBM	max. 65 g/l)
		Thick Bed Mortar- THBM 40 (Grey)	
		Thick Bed Mortar- THBM 40	
		(White)	
		Tile Joint Filler – TJF A	
		Tile Joint Filler – TJF B	
		Recon PH (2K)	
		Recon PH	





		Recon PH (M)	
		Recon PH (FS)	1
		Recon GP]
		Recon GP55	1
		Recon GPFS]
		Tilex LM (HS)	Part A - Water based polymer +
		Tilex LM (TB)	Part B — Cement based
		Tilex Grout LM	VOC (Al Sa'fat DGBES limit is
		Thex Glout Livi	max. 65 g/l)
		Nano Grout SG – Paste (Epoxy	
		Based)	
13		Recon FCE (Eposxy Based)	Solvent Free Epoxy Adhesive
	Multi-Purpose Construction	FitBond EA	VOC (Al Sa'fat DGBES limit is
		NanoGrout SG Pourable	- max. 70 g/l)
	Adhesive	ReCon LVE	1
		Recon FCE (WB)	Water Base Epoxy Adhesive
		51.0 1.000	VOC (Al Sa'fat DGBES limit is
		FitBond SBR	max. 70 g/l)

- NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.
- NOTE 2: The above products shall bear the DCL Conformity Mark.
- NOTE 3: For colors/types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-GBRS.
 - SRI Class 1 (≥ 78) "Can be Used in 75 100% of surface to be coated Sloped or Flat Roof"
 - SRI Class 2 (29<78) "Can be Used in 75 100% of surface to be coated Sloped Roof"
 - SRI Class 3 (< 29 or untested) "Can be Used in 0 25% of surface to be coated Sloped or Flat Roof provided the remaining area is Class 1 or 2"





SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020619

- o LRV Class 1 (≥45) "Can be used in 75-100% of surface to be /painted/coated"
- LRV Class 2 (<45 or untested) "Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1".

Original Issue Date: 24 July 2018
Current Issue Date: 24 July 2020
Valid Until: 23 July 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department