

# CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality  
hereby attests that the product(s)

## Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

**STONCOR MIDDLE EAST LLC**

**P.O. BOX 3034, Al Qouz Industrial Area 3 Dubai, UAE**

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

## 2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer  
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN  
Director, Dubai Central Laboratory Department  
Dubai Municipality



Certificate No: CL18020630  
Valid Until: 24/09/2021



Current Issue Date: 25/09/2020  
Original Issue Date: 25/09/2018



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.  
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



**DUBAI CENTRAL LABORATORY DEPARTMENT**  
**DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION**  
**FOR CERTIFICATE NO. CL18020630**

**Certificate Issued To** **STONCOR MIDDLE EAST LLC**  
P.O. BOX 3034, Al Qouz Industrial Area 3 Dubai, UAE.

**Applicable Standard Specification:** 2017 Al Sa'fat Dubai Green Building Evaluation System

**Applicable Specific Rules:** **DM-DCLD-RD-DP21-2180 (IC)** - Specific Rules for FA  
Certification of Low Emitting Materials as per Al Sa'fat – Dubai  
Green Building Evaluation System

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Binding Primer	Deckshield SF	Solvent Base for Interior/Exterior Application VOC (Al Sa'fat-DGBES limit is max. 750 g/l)
2	One Pack Performance Coating	Deckshield Concrecoat	Water Base for Interior/Exterior Application VOC (Al Sa'fat-DGBES limit is max. 140 g/l)
3	Two Pack Reactive Performance Coating for Specific End such as floor	Prostruct WB Clear	Water Base for Interior/Exterior Application VOC (Al Sa'fat-DGBES limit is max. 140 g/l)
		Flowfresh Coating	
		Flowfresh Primer	
		Flowfresh RT/HT/MF/SL	
		Flowfresh Cove	
		Deckshield UV	Solvent Base for Interior/Roofing Application VOC (Al Sa'fat-DGBES limit is max. 500 g/l)  Color: <b>Light Gray</b> SRI Class 2 - can be used in 75-100 % of surfaced to be coated - Sloped Roof (See Note 3)
		Deckshield Finish	
		Deckshield ED Membrane	
		Stonclad GS	
		Deckshield Linemarker	
		Deckshield Putty	
		Stonclad HT	
		Stonclad UT	
		Stonclad UR	
		Stonkote GS4	
		Stonkote HT4	



## DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020630

		Stonglaze E4	<p>Color: <b>Dark Gray</b></p> <p>SRI Class 3 - can be used in 0-25% of surfaced to be coated - Sloped or Flat Roof</p> <p>(See Note 3)</p>
		Urethane Primer	
		Standard Primer	
		HT Primer	
		Carboguard 1340	
		Carbothane 133HB	
		Prostruct 959	
		Prostruct 959 SL	
		Deckcoat EP	
		Flowcoat SF41	
		Flowcoat SF150	
		Flowprime	
		Flowshield SL	
		Flowshield Quartz	
		Flowshield LXP HD	
		Flowtex HT	
		Peran STC	
		Mondeco	
		Prostruct PU Line Marker	

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above products shall bear the DCL Conformity Mark.

NOTE 3: For colors/types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of Al Sa'fat.

- SRI Class 1 ( $\geq 78$ ) – “Can be Used in 75 - 100% of surface to be coated – Sloped or Flat Roof”
- SRI Class 2 ( $29 < 78$ ) - “Can be Used in 75 - 100% of surface to be coated – Sloped Roof”
- SRI Class 3 ( $< 29$  or untested) – “Can be Used in 0 – 25% of surface to be coated – Sloped or Flat Roof provided the remaining area is Class 1 or 2”
- LRV Class 1 ( $\geq 45$ ) – “Can be used in 75-100% of surface to be /painted/coated”
- LRV Class 2 ( $< 45$  or untested) – “Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1”.



**DUBAI CENTRAL LABORATORY DEPARTMENT  
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION**

**FOR CERTIFICATE NO. CL18020630**

Original Issue Date: 25 September 2018  
Current Issue Date: 25 September 2020  
Valid Until: 24 September 2021

**ARIF HUSAIN AL MARZOOQI**

Products Conformity Assessment Section Manager  
Dubai Central Laboratory Department