



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

ANCHOR ALLIED FACTORY L.L.C. BRANCH 3 P.O. Box 21152, Emirates Industrial City, Sajjah, Sharjah, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: CL18020574 Valid Until: 14/04/2021



Current Issue Date: 15/04/2020 Original Issue Date: 15/04/2018



DM-DCLD-F-IC-2031 Rev 17

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020574

Certificate Issued To: ANCHOR ALLIED FACTORY L.L.C. BRANCH 3

P.O. Box 21152, Emirates Industrial City, Sajjah, Sharjah,

UAE

Applicable Standard Specification: 2017 Al Sa'fat – Dubai Green Building Evaluation System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180-(IC) Specific Rules for FA

Certification of Low Emitting Materials as per Al Sa'fat -

Dubai Green Building Evaluation System.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS		
THE PRODUCTS PRODUCED IN "ANCHOR ALLIED FACTORY - L.LC - BRANCH 3", SHARJAH.					
1	ARCHITECTURAL SEALANT	ASMACO GOLD UNIVERSAL MULTI FOAM B1			
		GRADE	Sealant for Specific Application		
		ASMACO GOLD UNIVERSAL MULTI FOAM B2	VOC (Al Sa'fat DGBES limit is		
		GRADE	Max 250 g/l)		
		ASMACO GOLD UNIVERSAL MULTI FOAM			
	THE PRODUCTS	PRODUCED IN "ANCHOR ALLIED FACTORY - L.LC",	RAS AL KHAIMAH		
(External/Outsourced Production Facility)					
	ONE PACK PERFORMANCE COATING (SUB-CATEGORY: 9)	ASMACOAT WP 900	Solvent Base Coatings		
			for Interior/Exterior intermediate coatings		
			Applications		
			(Coating - Other Types)		
			VOC (Al Sa'fat DGBES limit is		
			Max.500 g/l)		
		ASMACOAT WP 600 (White Color)	Water Base Coatings for		
1			Exterior applications		
			(Roof Coating)		
			VOC (Al Sa'fat DGBES limit is		
			max.140g/l)		
			SRI Class 1 (<u>></u> 78) – "Can be Used in 75 -		
			100% of surface to be coated – Sloped or		
			Flat Roof"		
			(See Note 3)		
	ARCHITECTURAL SEALANT	ASMACO 2670			
		ASMACO GLASS			
		ASMACO FIRESTOP SILICONE SEALANT	<u> </u>		
		ASMACO INTUMESCENT ACRYLIC SEALANT	Sealant for Specific Application		
2		ASMACO PU 90			
		NEOFLEX PU 25LM	VOC (AI Sa'fat DGBES limit is		
		ASMACRYL 47	Max 250 g/l)		
		ASMACRYL 52			
		GYPROC SEALANT			
		CRAYCOAT ACRYLIC DUCT SEALANT			





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL18020574

		ASMACO 2500	VOC (Al Sa'fat DGBES limit is
3	SEALANTS OTHER	ASMACO GP	Max 420 g/l)
		ASMACO 2540	
4	ADHESIVE-SPECIALTY APPLICATIONS	EASY PRE-INSULATED DUCT SYSTEM ADHESIVE	(Sheet Applied Rubber Lining Operations) VOC (Al Sa'fat DGBES limit is
		ASMACO GOLD CONTACT ADHESIVE	Max 850 g/l)

NOTE1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE2: The above product shall bear the DCL Conformity Mark.

NOTE3: For colors/types not covered by the Scope, SRI shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the 2017 Al Sa'fat –Dubai Green Building Evaluation System.

- SRI Class 1 (≥ 78) "Can be Used in 75 100% of surface to be coated Sloped or Flat Roof"
- o SRI Class 2 (29<78) "Can be Used in 75 100% of surface to be coated Sloped Roof"
- SRI Class 3 (< 29 or untested) "Can be Used in 0 25% of surface to be coated Sloped or Flat Roof"

Original Issue Date: 15 April 2018
Current Issue Date: 15 April 2020
Valid Until: 14 April 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department