



### CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

### **Low Emitting Materials**

(Details as per the attached Scope of Certification)

manufactured by:

**HILTI GmbH** 

86916 Kaufering, Germany

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

#### 2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**





Certificate No: CL20020730 Valid Until: 22/02/2021



Current Issue Date: 23/02/2020 Original Issue Date: 23/02/2020

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



DM-DCLD-F-IC-2031 Rev 16





# DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION-REVISION 01 FOR CERTIFICATE NO. CL20020730

Certificate Issued To: HILTI GmbH

86916 Kaufering, Germany

**Applicable Standard Specification**: 2017 Al Sa'Fat – Dubai Green Building Evaluation

System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180 (IC) - Specific Rules

for FA Certification of Low Emitting Materials as per Al Sa'fat – Dubai Green Building Evaluation

**System** 

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Coatings (other types)	Firestop coating CP 670	One-pack performance coatings (Sub-category 9)  (Solvent Free-WB)  (Internal)  With maximum VOC = 140 g/L
2	Sealant	Firestop joint spray CFS-SP WB Firestop foam CP 620 Firestop sealant FS- One/ FS-One Max Firestop joint filler CP 606	Architectural Sealant (Internal/External) With maximum VOC = 250 g/L
3	Adhesives*	HIT-RE 500 V3 Injectable Adhesive HIT-RE 100 Injectable Adhesive HIT-HY 200 Injectable	Multi-Purpose Construction Adhesives (Internal/External)  With maximum VOC = 70 g/L





## DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION-REVISION 01 FOR CERTIFICATE NO. CL20020730

	Adhesive
	HIT-HY 270 Injectable
	Adhesive
	HIT-HY 170 Injectable
	Adhesive
	HVU 2 Adhesive
	Capsule

<sup>\*</sup>newly added products

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same Certificate Number.

NOTE 2: The above product shall bear the DCL Conformity Mark (applied on each product or on the packaging).

NOTE 3: This supersedes the Scope of Certification issued on 23 February 2020.

Original Issue Date : 23 February 2020

Current Issue Date : 16 March 2020

Valid Until : 22 February 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department