



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

Low Emitting Materials

(Details as per the attached Scope of Certification)

manufactured by:

AL MUTATHAWIR INSULATION MATERIALS INDUSTIRES LLC Plot 4/2035 Al Hanoo Area, Saja'a Industrial Oasis, Sharjah, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: Valid Until:

CL20020739 30/03/2022



Current Issue Date: 31/03/2021 Original Issue Date: 31/03/2020



DM-DCLD-F-IC-2031 Rev 18

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020739

Certificate Issued To AL MUTATHAWIR INSULATION MATERIALS INDUSTRIES LLC

Plot 4/2035 Al Hanoo Area, Saja'a Industrial Oasis, Sharjah, UAE

Applicable Standard Specification: 2017 Al Sa'fat - Dubai Green Building Evaluation System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180 (IC) Specific Rules for FA Certification

of Low Emitting Materials as per 2017 Al Sa'fat - Dubai Green

Building Evaluation System.

	Danang Evaluation Systems				
S/N	Product Description	Brand Name	Product Details		
1	Interior/ Exterior trim and cladding paints for wood and metal (sub category 4)	Advacoat 250	Water Based for Interior/Exterior Applications:		
		Advacryl 120	VOC (Al Sa'fat-DGBES limit is max.130 g/l) Formaldehyde \leq 10 mg/kg WHITE COLOR		
		Advaseal 2000	Class 1: LRV is ≥ 45% (suitable as exterior coating for buildings) (See Note 3)		
	Primers (sub category 7)	Advaprim Emulsion	Water Based for Interior/Exterior		
		Advaproof Emulsion SBR	Applications:		
		Advaproof Emulsion SG	VOC (Al Sa'fat-DGBES limit is max.30 g/l) Formaldehyde \leq 10 mg/kg		
2		Advatex 2000	Heavy metals: Cadmium and Chromium (Al Sa'fat-		
		Advafoamcrete	DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat-DGBES limit <100 mg/Kg)		
	Binding Primers (Sub-category 8)	Novaseal Coating	Water Based for Interior/Exterior Applications: VOC (Al Sa'fat-DGBES limit is max. 30 g/l)		
3		Advaprim Solvent	Solvent Based for Interior/Exterior Applications:		
			VOC (Al Sa'fat-DGBES limit is max. 750 g/l) Heavy metals: Cadmium and Chromium (Al Sa'fat-DGBES limit < 500 mg/Kg), Arsenic, Mercury and Lead (Al Sa'fat-DGBES limit < 100 mg/Kg)		





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020739

4	One Pack Performance Coating (Sub category 9)	Advabrush - 1	Water Base for Interior/Exterior Applications: VOC (Al Sa'fat-DGBES limit is max. 140 g/l)
		Advabrush - 2	Formaldehyde ≤ 10 mg/kg
		Advaline	WHITE COLOR Class 1 : SRI is ≥78 (suitable for steep sloped
		Advathane PU Coating	surface and for flat or low sloped surface) Class 1: LRV is ≥ 45% (suitable as exterior
		Emulsion	coating for buildings) (See Note 3)
		Advathane PU Coating Solvent	Solvent Base for Interior/Exterior Applications: VOC (Al Sa'fat-DGBES limit is max. 500 g/l)
	Two Pack Reactive Performance Coating (Sub category 10)	Advapoxy Flooring 1500	Solvent Base for Interior/Exterior
5		Advapoxy Flooring 3000	Applications: VOC (Al Sa'fat-DGBES limit is max. 500 g/l)
		Advapoxy Clear	100 (11 30 100 B 30 E 3 11 11 11 11 11 11 11 11 11 11 11 11 1
6	Sealant	Advamastic	Architectural Sealant VOC (Al Sa'fat-DGBES limit is max 250 g/l)

- **NOTE 1**: This document forms part of the Certificate of Product Conformity bearing the same certificate number.
- **NOTE 2**: The above product shall bear the DCL Conformity Mark.
- NOTE 3:For colors/types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the Al Sa'Fat Dubai Green Building Evaluation System.
 - SRI Class 1 (> 78) "Can be Used in 75 100% of surface to be coated Sloped or Flat Roof"
 - SRI Class 2 (29<78) "Can be Used in 75 100% of surface to be coated Sloped Roof"
 - SRI Class 3 (< 29 or untested) "Can be Used in 0 25% of surface to be coated Sloped or Flat Roof provided the remaining area is Class 1 or 2"





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020739

- LRV Class 1 (=>45) "Can be used in 75-100% of surface to be /painted/coated"
- LRV Class 2 (<45 or untested) "Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1".

Original Issue Date: 31 March 2020
Current Issue Date: 31 March 2021
Valid Until: 30 March 2022

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department