

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Mineral Fiber Block and Board Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

FUJAIRAH ROCKWOOL FACTORY

P.O. BOX 211, AL HAYL INDUSTRIAL AREA, FUJAIRAH, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

ASTM C612 - 2014

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



for / ENGR. AMIN AHMED AMIN
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL06020019
Valid Until: 11/10/2021



Current Issue Date: 12/10/2020
Original Issue Date: 12/10/2006



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL06020019

Certificate Issued To: FUJAIRAH ROCKWOOL FACTORY
P.O. Box 211, Al Hayl Industrial Area, Fujairah, U.A.E.

Applicable Standard Specification: ASTM C 612: 2014 - Standard Specification for Fiber Block and Board Thermal Insulation

Applicable Specific Rules: DM-DCLD-RD-DP21-2108 (IC) "Specific Rules for Certification of Mineral Fiber Block and Board Thermal Insulation (ASTM C 612: 2014) Through Factory Assessment".

S/N	Product Description	Brand Name	Product Details
1.	Mineral Rockwool Board/Slab Thermal Insulation	Fujairah Rockwool Slabs (SXXX)	Type IB and Type II without facing k-value: 0.039 W/(m-°K) Nominal Density Range: 40 - 200 kg/m ³ Nominal Thickness: 25 - 200 mm
		Fujairah Rockwool Slabs (S2XX & S22X)	Type IB and Type II with aluminum foil facing k-value: 0.039 W/(m-°K) Nominal Density Range: 40 - 200 kg/m ³ Nominal Thickness: 25-200 mm
		Fujairah Rockwool Slabs (SBXX & SBBX)	Type IB and Type II with black aluminum foil facing k-value: 0.039 W/(m-°K) Nominal Density Range: 40 - 200 kg/m ³ Nominal Thickness: 25-200 mm

Note 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.
Note 2: The above product shall bear the DCL Conformity Mark.
Note 3: Maximum k-value measured at 35°C temperature and 60% relative humidity condition.

Original Issue Date: 12 October 2006
Current Issue Date: 12 October 2020
Valid Until: 11 October 2021



ARIF HUSAIN AL MARZOOQI
Products Conformity Assessment Section Manager
Dubai Central Laboratory Department