



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

EMIRATES INDUSTRIAL PANEL LLC

Plot No. 598 1106, Dubai Investment Park (DIP), Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13165: 2012

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: CL09020104 Valid Until: 20/07/2021



Current Issue Date: 21/07/2020 Original Issue Date: 21/07/2009



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.









DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL09020104

Certificate Issued To: Emirates Industrial Panel LLC

Plot No. 598 1106, Dubai Investment Park (DIP), Dubai,

UAE

Applicable Standard Specification: BS EN 13165:2012 –Thermal insulation products for

buildings - Factory made rigid polyurethane (PU) foam

products - Specification

Applicable Specific Rules: DM-DCLD-RD-DP21-2124 (IC) "Specific Rules for

Certification of Factory Made Rigid Polyurethane (PU) Foam Thermal Insulation Products (as per BS EN 13165:2012)

Through Factory Assessment".

S/N	Product	Brand	Product Details
	Description	Name	
1	Factory Made	EIP	PIR Insulation foam
	Rigid	B. HIGH	Thickness= Class T2; Length= > 3000 ±10 mm & < 3000 ±5
	Polyisocyanurate	PIR	mm; Width = $600 \text{ to } 1140 \text{ mm w/} \pm 3 \text{ mm}$; Apparent Density =
	(PIR) foam		$40 \pm 3 \text{ kg/m}^3$; Thermal conductivity = Initial value 0.024 (max)
		EIP	and Aged value 0.025W/(m*K) <i>(See Note 1)</i>
	CFC FREE	D. HIGH	
	(See Note 5)	PIR	PIR-EN 13165-T2-DS(TH)3-CS(10/Y)100 MU10 -190
		EIP	Manufactured as sandwich panels thermal insulation, with hot
		HIGH	dipped galvanized, zinc coated steel as inner and outer skin
		PIR	facing.

Note 1: Maximum k-value measured at 35°C temperature and 60% relative humidity condition

Note 2: This certification covers only the PIR foam within the panel

Note 3: This document forms part of the Certificate of Product Conformity bearing the same certificate number.





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL09020104

Note 4: The above product shall bear the DCL Conformity Mark applied on each individual product

Note 5: In compliance with 2017 Al Sa'fat Dubai Green Building Evaluation System

Original Issue Date : 21 July 2009

Current Issue Date : 21 July 2020

Valid Until : 20 July 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department