



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

In-situ Formed Sprayed PUR/PIR Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

ADVANCE COMBO SYSTEM INSULATION Business Park Bldg. Ofc. No. 504-53, P.O. Box 233833, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 14315-1: 2013

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: CL16020385 Valid Until: 13/04/2021



Current Issue Date: 14/04/2020 Original Issue Date: 27/07/2016



DM-DCLD-F-IC-2031 Rev 17

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.









DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL16020385

Certificate Issued To: ADVANCE COMBO SYSTEM INSULATION

Business Park Bldg. Ofc. No. 504-53, P.O. Box 233833,

Dubai, UAE

Applicable Standard Specification: BS EN 14315-1:2013 – Thermal insulating products for

buildings In-situ formed sprayed polyurethane (PUR) and

Polyisocyanurate (PIR) foam products

Applicable Specific Rules: DM-DCLD RD-DP21-2187 (IC) "Specific Rules for

Certification of In Situ Formed Sprayed Polyurethane and Polyisocyanurate Foam Products (as per BS EN14315-

1:2013) Through Factory Assessment".

S/N	Product Description	Brand Name	Product Details
1	In-Situ Formed	ADVANCE	Min. Density : 40 kg/m³
	Sprayed	СОМВО	Thickness = 30 mm-150 mm
	Polyurethane		*k-value: 0.028 W/(K•m) @ 35 °C & 60% RH
	(PUR) Foam Products		With a minimum Compressive Strength of 100 kPa
	"CFC Free" **		Dimensional Stability (DS(TH)2
			Product Code:
			PU EN14315-1-CS(10/Y)100-DS(TH)2-MU25

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same Certificate Number.

NOTE 2: * Maximum k-value measured at 35°C temperature and 60% relative humidity Condition.

NOTE 3: ** CFC Free as per declaration from the company, in compliance with Clause 701.01 (1) of the 2017

Al Sa'fat Dubai Green Building Evaluation System.

Original Issue Date: 27 July 2016

Current Issue Date: 14 April 2020

Valid Until: 13 April 2021

ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department