



#### CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality hereby attests that the product(s)

#### **Low Emitting Materials**

(Details as per the attached Scope of Certification)

manufactured by:

#### LATICRETE MIDDLE EAST LLC RAK CERAMICS BLDG. 3RD FLOOR AL JAZEERA AL HAMRA - RAK

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

#### 2017 AL SA'FAT DUBAI GREEN BUILDING EVALUATION SYSTEM

Accordingly, DCLD hereby authorizes the above manufacturer to affix the DCL Product Conformity Mark on the above-mentioned product(s).

> for / ENGR. AMIN AHMED AMIN Director, Dubai Central Laboratory Department **Dubai Municipality**



Certificate No: CL20020733 09/03/2022 Valid Until:



Current Issue Date: 10/03/2021 Original Issue Date: 10/03/2020



DM-DCLD-F-IC-2031 Rev 18

The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate. This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.







### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020733

Certificate Issued To LATICRETE MIDDLE EAST LLC

RAK CERAMICS BLDG. 3rd FLOOR AL JAZEERA AL HAMRA - RAK

Applicable Standard Specification: 2017 Al Sa'fat Dubai Green Building Evaluation System

Applicable Specific Rules: DM-DCLD-RD-DP21-2180-(IC) Specific Rules for Certification

of Low Emitting Materials (Coatings, Adhesives & Sealants) As per the 2017 Al Sa'fat Dubai Green Building Evaluation System.

| S/N | Product<br>Description  | Brand Name   | Product Details   |
|-----|---|--|---|
| 1   | One-pack performance coatings (Sub-category 9) (other types)                                | 9235 Waterproofing Membrane 9237 Waterproofing Membrane Hydro Ban®   | Water Base Coatings for Interior Application (Waterproofing undercoat)  VOC (GBRS limit is max.140 g/l)   |
|     |   | Level Primer Admix & Primer  | Water Base Coatings for interior Application (Underlayer floor coating) VOC (GBRS limit is max.140 g/l)   |
|     |   | STONETECH® BULLETPROOF SEALER®  190 SEALER   | Water Base Coatings for Interior Application (Tile & Stone top sealer)  VOC (GBRS limit is max.140 g/l)   |
|     |   | STONETECH <sup>®</sup> Impregnator Pro <sup>®</sup> Sealer<br>STONETECH <sup>®</sup> Enhancer Pro <sup>tm</sup> Sealer   | Solvent Base Coatings for Interior Application (Tile & Stone top sealer)  VOC (GBRS limit is max.140 g/l) |
| 2   | Two Pack Reactive Performance Coating for Specific End Use such as Floors (Sub-category 10) | LATICRETE BASE  LATICRETE CLEAR  LATICRETE FLOW  LATICRETE GUARD  LATICERTE PRIMER  LATICRETE SEALER  LATICRETE CLEAR PU | Solvent Base Coatings for Interior Application (Floor-Top coating) VOC (GBRS limit is max.140 g/l)        |





## SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020733

| FOR CERTIFICATE NO. CL20020733 |           |  |   |  |  |
|--------------------------------|-----------|--|---|--|--|
|                                |           | LEVEL SUPERCAP SC 500 86 LATILEVEL LATASCREED 100  | Water Base Coatings for Interior Application (Underlayer floor coating) VOC (GBRS limit is max.140 g/l)             |  |  |
|                                |           | DRYTEK <b>9400</b><br>LEVEL DL PLUS  | Water Base Coatings for Interior Application (Floor-Top coating) VOC (GBRS limit is max.140 g/l)                    |  |  |
|                                |           | LATAFINISH WALL PUTTY  | Water Base Coatings for Interior Application (Underlayer finish before painting) VOC (GBRS limit is max.140 g/l)    |  |  |
|                                |           | 302 Waterproof Slurry<br>Aqua Barrier  | Water Base Coatings for Interior Application (Waterproofing undercoat) VOC (GBRS limit is max.140 g/l)              |  |  |
| 5                              | ADHESIVES | 305 TILE GLUE 315 TILE ADHESIVE 317 FLOOR AND WALL 325 PREMIUM TILE ADHESIVE 335 PREMIUM PLUS TILE ADHESIVE 254 PLATINUM / 254 PLATINUM-RAPID 226 THICK BED MORTAR 290 PREMIUM FLOOR & WALL 220 MARBLE AND GRANITE THICK BED ADHESIVE 211 CRETE FILLER POWDER 211 CRETE FILLER POWDER 211 CRETE FILLER POWDER S2 + 4237 LATEX THIN-SET MORTAR ADDITIVE S2 73 CRETE ADMIX 3701 MORTAR ADMIX 4237 LATEX THINSET MORTAR ADDITIVE 3642 LATEX CONCENTRATE 3701 FORTIFIED MORTAR BED | Water Base Adhesives for Specific Application (Cementitious Tile & Stone Adhesives) VOC (GBRS limit is max. 80 g/l) |  |  |





### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020733

|  |  | Solvent Base Adhesives                 |
|--|--|--|
|  | LATAPOXY 300 ADHESIVE  LATAPOXY 310 STONE ADHESIVE  LATALASTIK | for Specific Application               |
|  |  | (Polymer based Tile & Stone Adhesives) |
|  |  | VOC (GBRS limit is max. 80 g/l)        |
|  | 1500 SANDED GROUT  | Water Base Adhesives                   |
|  | 1600 UN SANDED GROUT   | for Specific Application               |
|  | Permacolor grout   | (Cementitious Tile joint grout)        |
|  | PERMACOLOR SELECT GROUT  | VOC (GBRS limit is max. 80 g/l)        |
|  | 1776 GROUT ADMIX PLUS  |  |
|  |  | Water Base Adhesives                   |
|  |  | for Specific Application               |
|  | *SPECTRALOCK PRO PREMIUM GROUT STELLAR GROUT                   | (Aqueous Polymer based Tile & Stone    |
|  |  | joint grout)                           |
|  |  | VOC (GBRS limit is max. 80 g/l)        |
|  | LATAPOXY SP-100  | Solvent Base Adhesives                 |
|  |  | for Specific Application               |
|  |  | (Aqueous Polymer based Tile & Stone    |
|  |  | joint grout)                           |
|  |  | VOC (GBRS limit is max. 80 g/l)        |
|  | LATAPOXY <sup>®</sup> 2000 INDUSTRIAL EPOXY GROUT              | Solvent Base Adhesives                 |
|  |  | for Specific Application               |
|  |  | (Polymer based Tile & Stone joint      |
|  |  | grout)                                 |
|  |  | VOC (GBRS limit is max. 80 g/l)        |

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark.

NOTE 3: For colors/Types not covered by the Scope, SRI and LRV shall be tested and classified based on the application of the product in the construction site to ensure that it meets the requirements of the DM-GBRS.

- SRI Class 1 (> 78) "Can be Used in 75 100% of surface to be coated Sloped or Flat Roof"
- SRI Class 2 (29<78) "Can be Used in 75 100% of surface to be coated Sloped Roof"
- SRI Class 3 (< 29 or untested) "Can be Used in 0 25% of surface to be coated Sloped or Flat Roof provided the remaining area is Class 1 or 2"
- LRV Class 1 (=>45) "Can be used in 75-100% of surface to be /painted/coated"
- LRV Class 2 (<45 or untested) "Can be used in 0-25% of surface to be painted/coated provided the remaining area is Class 1"

NOTE 4:  $\star$  - Revised with new product name.





## SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL20020733

Original Issue Date : 10 MARCH 2020

Current Issue Date : 10 MARCH 2021

Valid Until : 09 MARCH 2022

**ARIF HUSAIN AL MARZOOQI** 

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department